SPRAY URKI**FILLER**

1K HS Filler

DESCRIPTION

Single component spray filler used for fast repair of vehicles and machinery in general. It stands out for its easy application, filling power, quick drying and easy sanding. In thin layers, it can be repainted without prior sanding. Recoatable with all types of topcoats.

COLORS

URKI**FILLER**	7035	7040	7016

SURFACE PREPARATION

Before starting to apply it, correctly sand, clean and degrease the surfaces to be repaired with

SD-7 10 or URA**SOL 8905** degreasers.

On 2K polyester putties, sand and degrease before application.

On steel degrease and remove rust. The use of this filler on thermoplastic acrylic enamels is not recommended.

Can be repainted with 1K and 2K topcoats and basecoats, both water- and solvent-based.

USE

Shake the can for 2-3 minutes before using URKI**FILLER** spray. Apply 2-3 coats, leaving 5-10 minutes between them. After use, invert the spray and clean the valve.

APPLICATION

Shake can	2-3’
Painting distance	20-30 cm
Number of coats Total thickness	2-3 coats 15-30 µm
Flash time	5-10’
Drying Time 20°C	30’
Sanding 20°C	P400 Basecoat/P320 Topcoat 2 h

SAFETY INSTRUCTIONS

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

CAUTION: Under no circumstances should the packaging exceed 50°C.

VOC

The VOC content of SPRAY URKI**FILLER** is a maximum of 840 g/l in compliance with the European regulation 2004/42/CE IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**