TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia (SPAIN)
Tel.: +34 +34 943 74 28 00
Fax: +34 +34 943 74 06 03
www.besa.es

SPRAY URKISOL SD-7 10

SLOW DEGREASER

Edition: 021 2021/06

Cod: 9000000710097.00000.021

APPLICATION

Slow degreaser formulated to clean grease, oil and other polluting agents before painting.
Can also be used before and after sanding in several layers processes.
VOC content lower than 840 g/l (2004/42/CE) IIB (E)

APPLICATION INSTRUCTIONS

Shake the can before using it.
Spray a layer of SPRAY URKISOL SD-7 10 all over the surface and clean it manually with a cloth (this cloth must be changed regularly.
You can also degrease by pouring the degreaser from SPRAY URKIS-SOL SD-7 10



Painting range
20-30 cm



5-10 min

Having used the spray, turn it upside down and press in order to clear the nozzle.

COMPOSICIÓN

Type of product	Aliphatic hydrocarbons, aromatic hydrocarbons

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30ºC recommended.
Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.

BERNARDO ECENARRO,S.A. is free for making any modification, in any moment, of the characteristics of the product. In this case, a new Technical Data Sheet will be edited.
Responsabilities will not be accepted if they are due to the non observation of the conditions marked.