TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia (SPAIN)
Tel.: +34 +34 943 74 28 00
Fax: +34 +34 943 74 06 03
www.besa.es

SPRAY URKI-ETCH

UNIVERSAL 1K PRIMER

Edition: 020 2017/12

Cod: 3700607040097.00000.020

APPLICATION

Universal 1k primer with adhesion on steel, galvanized steel, electro-zinc and aluminum. Its fast drying, excellent adhesion and recoatability focus this primer on touching up in the Boiler manufacturing, Industrial Vehicle, Agricultural Machinery, Metallic Structure, etc.

It offers good adhesion on plastic supports such as PA6, PVC, MA, PC and ABS, Epoxy, Polyester and Carbon Fiber.

SURFACE PREPARATION

The metallic supports, as well as the plastics, must be correctly prepared before the application (sanded, cleaned and degreased).

APPICATION INSTRUCTIONS

Shake the can during 2-3 minutes before use the SPRAY URKI-ETCH
Apply 1 coat and let it dry before each sanding operation
After use, turn upside down the can and clean the valve


Painting range 20-30 cm


10-15my


5-10 min


Dry 20 min.

FEATURES OF DRY FILM

Colour	Grey 7040
Gloss 60º-60º	Matt <5%
Second layer	2 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30ºC recommended.
CAUTION: Do not expose the can to temperatures over 50ºC.
Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.

BERNARDO ECENARRO,S.A. is free for making any modification, in any moment, of the characteristics of the product. In this case, a new Technical Data Sheet will be edited.
Responsabilities will not be accepted if they are due to the non observation of the conditions marked.