SPRAY **NEGRO MATE J-13**

J-13 Matt Black



DESCRIPTION

Quick-drying enamel for interior and exterior use. It stands out for its high coverage, good body, quick drying and matt appearance.

It is ideal for retouching and finishing small body parts and other works in the industry in general.

COLORS

J-13 MATT BLACK	**J-13**

SURFACE PREPARATION

On steel: The surfaces to be painted must be properly derusted and degreased.

For a better adhesion and protection of the support, it can be previously primed with F-29 or F-809.

On old paint, sand and degrease previously. Do not apply on synthetic paints (alkyd base).

USE

Shake the can for 2-3 minutes before using SPRAY **NEGRO MATE J-13.** Apply 2-3 coats, leaving 5-10 minutes between coats. After use, invert the can and clean the cap.

APPLICATION

 Shake can	2-3'
 Painting distance	20-30 cm
 Number of coats Total thickness	15-25 µm
 Flash time	5-10'
 Drying Time 20°C	45'
 % Gloss 60°- 60°	Matt

Can be repainted after 24 hours.

SAFETY INSTRUCTIONS

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

CAUTION: Under no circumstances should the packaging exceed 50°C.

VOC

The VOC content of SPRAY **NEGRO MATE J-13** is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E)(840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**