TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia (SPAIN)
Tel.: +34 +34 943 74 28 00
Fax: +34 +34 943 74 06 03
www.besa.es

URKI-KOMBI

1 K NC SEALER

Edition: 021 2021/04

Cod: 5215007035.00000.021

APPLICATION

URKI-KOMBI is a ready-to-use sealer, based on nitrocellulose resins. Designed for Spot Repair to collect minor imperfections such as scratches, blisters, pinholes, impacts, etc. It is also very effective in filling in small pinholes in spoilers and Fiberglass parts.
The product stands out for its:
- Easy application
- Fast drying
- Soft, silky and very flexible surface
- Lack of shrinkage in repaired areas

Can be applied on polyester putties or acrylic type primers and fillers. Also on steel, aluminum and zinc covered surfaces.

PHYSICAL PROPERTIES

Density at 20ºC (g/cc)	1,68 ± 0,03
Grinding Fineness (µ)	Without lumps
Supply viscosity at 20ºC	Tixotropic
V.O.C. (g/l)	< 540 (Ready to use) - (2004/42/CE) IIB (C) (540)
Type of produtc	Nitrocellulose
Colour	Grey 7035

SURFACE PREPARATION

The surface to be repaired must be degreased and sanded, both on metallic surfaces, putties and fillers.

APPICATION INSTRUCTIONS

Application: Spatula.
Application in thin layers. Time between layers 20-30 min. Not recommended to exceed 70-80m total.


Maximum 80 my
in thin layers


30-45'


P-240
P-400

FEATURES OF DRY FILM

Theoretical yield (m²/l)	
Gloss 60º-60º	Matt
Second layer	1 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30ºC recommended.
Can life: **12 months** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.

BERNARDO ECENARRO,S.A. is free for making any modification, in any moment, of the characteristics of the product. In this case, a new Technical Data Sheet will be edited.
Responsabilities will not be accepted if they are due to the non observation of the conditions marked.