

Outdoor RTD Probe (Transmitter) BTS(O)P

- ◆ Low cost
- ◆ Pt_x sensitive element
- ◆ 2-wire 4...20 mA output available
- ◆ IP66 protection class
- ◆ Robust aluminum enclosure
- ◆ Ready to use - no adjustments

The outdoor temperature probes BTSP and BTSP0 measure temperature by means of a Pt_x sensitive element mounted in a thin stainless steel stem for fast response. The BTSP0 model, in addition, converts the measured temperature into standard 4...20 mA 2-wire signal. Both models are enclosed in a freely mountable robust aluminum enclosure with IP66 protection class and are equipped with a PG7 cable gland for stable and protected electrical decoupling. Five different temperature measurement ranges from -50 °C and up to 100 °C as well as customer specified ranges are available. Thanks to their simplicity, small size, and affordable price, BTSP and BTSP0 are applicable for various outdoor applications, environment temperature control, climatic temperature measurement, etc.



Technical specifications

Input	
Incorporated RTD	Pt100 or Pt1000 ($w=1.385$)
Measurement range	-50...50 °C; 0...50 °C; -20...60 °C; 0...100 °C ⁽¹⁾ ; -50...100 °C ⁽¹⁾
Range on request	minimum span 50 °C
Output	
Signal type	4...20 mA, 2-wire
Linearity proportional to	measured value
Output at sensor burnout	32 mA
Output at sensor shorted	0.2 mA
Accuracy	
Electronic measurement error	0.2% from span or 0.2 °C ⁽²⁾
RTD measurement error	according to accuracy class
Non-linearity	within measurement error
Self-heating error	0.02%/mA at 24 V
Temperature drift	0.02% from span for 1 °C

⁽¹⁾ Not available for BTSP

⁽²⁾ Which is greater

Power supply	
Loop voltage	10...32 VDC
Admissible variations	1 Vp-p at 50 Hz
Maximum line load	750 Ω at 24V/20mA
Operating conditions	
Ambient temperature	-30...65 °C
Ambient humidity	5...95 %RH
EM compatibility	according to EN 61326
Design and materials	
Stem diameter	4 mm 5 mm
Stem length	20...60 mm 60...200 mm
Sensor sheath	stainless steel
Housing material	aluminum
Wiring	PG7 metal cable gland
Mounting	free
Protection class	IP66

Ordering code BTS(O)P - G2.G3.G6.G11 - #1

Code	Feature or option	Code values
G2	Sensor ⁽³⁾	RD - Pt100, RG - Pt1000
G3	Temperature range	T10 - -20...60 °C, T17 - -50...50 °C, T18 - 0...50 °C, T19 - 0...100 °C ⁽¹⁾ , T12 - -50...100 °C ⁽¹⁾ , TZ - other (specify, $\Delta T \geq 50$ °C)
G6	Stem length 'n' [mm]	20...200 (see table above)
G11	Accuracy class	A - 'A', B - 'B', C - '2xB'
#1	Options	X - none, OP - electrochemically polished sheath surface

⁽³⁾ Do not code for BTSP0