



ENVIRONMENTAL MONITORING & CONTROL



Measure,
Control and Log Data





- TRANSMITTER
- DISPLAY
- METER
- CONTROLLER

in one

BRHT is a new line of modern industrial devices, which integrates transmitters, displays, meters and controllers functionalities. Using the latest miniaturisation technologies these compact devices are able to be equipped with two independent universal inputs, two binary or two analogue outputs, as well as communication port RS-485 with Modbus protocol.




Within the **BRHT** range, models 200 and 400 have integrated temperature and relative humidity sensor. As well as an exceptionally wide working temperature range (-30 ÷ +120°C) they are also equipped with mathematical functions, which make it possible to transform measured values into others, e.g. to calculate dew point, sum or difference of two measured values.

A large built-in display and output signals mean that the **BRHT** units find applications in control systems. There are many industrial applications, where **BRHT** can act as stand-alone controller. It can also cooperate with master devices via Modbus protocol, being part of big network, which makes it perfect device for distributed monitoring system.

■ Applications

- food processing industry
- building HVAC automation
- warehouses, cold rooms
- glasshouses, breeding
- factories and manufacturing
- museums, archives, galleries
- server rooms, air-conditioned rooms
- weather stations



Measurement



The primary functionality of BRHT is taking measurements. Depending on needs and requirements, this compact device is equipped with top quality, precise and stable temperature and humidity sensors and/or with universal inputs that are standard for industrial automation. Thanks to its equipment the device guarantees a very high level of measurement reliability. Both version of probes - integrated and cable ones - are made of stainless steel. The sensors are protected with a replaceable PTFE or stainless steel mesh filter. The filter type is adjusted to a particular version of the probe.

Control




A proper reaction of a controller is triggered by measured values interpretation, which impacts the state of output signals. Users can choose between binary outputs and analogue outputs (current and voltage ones) to adjust their model to the requirements of a specific application. Due to that the device is characterised by a wide range of various outputs and the possibility of applying them in one unit. As a consequence, the BRHT meters can be used for digital or proportional controlling, and for combining both functions in one device as well.


Communication



What is required in case of more advanced measuring and controlling networks is communication between devices. For such applications we offer the RS-485 interface which is standard equipment supporting the Modbus RTU protocol. The free S-Config software is used for communication functionalities that facilitate the device's remote configuration without the need to use a local keyboard. Measured values and output states are shared in the Slave mode. It concerns more advanced applications with existing or required central steering and visualisation systems for the devices in the BRHT line.



Main features



- Replaceable filter made of PTFE or 316L mesh, 25 µm
- Universal inputs of a very wide spectrum of analogue signal types (I, U, RTD, TC)
- Binary and analogue outputs for indicating and controlling (1 or 2 E REL, I, U)
- Very clear 2.9" LCD display
- Indication of 1, 2, or 4 parameters on one screen
- Individual descriptions of measuring channels
- Optional elaboration of personalised graphic units, displayed at measurements (e.g.: m³, l/h, kPa, °F, etc.)
- Standard equipment: RS-485 Modbus RTU interface for integration with superordinate visualisation or control systems
- Device configuration performed by means of local buttons, optional remote controller or free S-Config 2 software
- Operating temperature: -30°C ÷ +80°C
- IP rate protection: IP 67 (version without display), IP 65 (version with display)

Typical measurements

for T or T+RH probes:



temperature



humidity



dew point

for universal inputs, e.g.:



CO₂



barometric pressure



flow



pH



redox

... and many more


Inputs configuration

- 1 x temp. or temp. + RH probe



°C or °C + RH


- 1 x temp. or temp. + RH probe
- 1 x universal (U, I, RTD, TC)



°C or °C + RH


Series 200, 400, 600

- 1 x universal (U, I, RTD, TC)



Series 100


- 2 x universal (U, I, RTD, TC)




Exemplary outputs configuration



- 2 x E REL
- 1 x RS-485




- 1 x AO (0-10V)
- 1 x E REL
- 1 x RS-485



- 1 x AO (0/4-20 mA)
- 1 x E REL
- 1 x RS-485



or



- 2 x AO (0-10V) or
- 2 x AO (0/4-20 mA)
- 1 x RS-485

Technical data



| Line | BRHT 100 | | BRHT 200 | | | BRHT 400 | | BRHT 600 | |
|--------------------------|---|---|---|---|--|---|---|---|--|
| Model | 100 | 211 | 212 | 213 | 421 / 422 | 612-XX-1 / 612-XX-3 | 612-XX-2 / 612-XX-4 | 621 / 622 | |
| Power supply | 24V DC (11 ÷ 36V DC), power consumption: 2.5 W max. | | | | | | | | |
| Display | none or graphic LCD, 128 x 64 points, with backlight | | | | | | | | |
| Type of probe | none | radial integrated, length 40 mm, Ø 18 mm, stainless steel 316L, PTFE filter cap | radial integrated, length 90 mm, Ø 18 mm, stainless steel 316L, PTFE filter cap | radial integrated, length 145 mm, Ø 18 mm, stainless steel 316L, PTFE filter cap | axial integrated, L=200 or 300 mm, Ø 12 mm, stainless steel 316L probe and filter cap | cable probe L=90 mm, Ø 18 mm, stainless steel 316L, PTFE filter cap | cable probe L=90 mm, Ø 18 mm, stainless steel 316L, PTFE filter cap | cable probe L=200 or 300 mm, Ø 12 mm, stainless steel 316L probe and filter cap | |
| Probe parameters | none | temp.: measuring range -30 ÷ 80°C, typ.err. ±0.5°C @ -10 ÷ 80°C temp. & humidity: measuring range -30 ÷ 80°C, typ.err. ±0.2°C @ 10 ÷ 60°C (±0.4°C @ -30°C; ±0.7°C @ 120°C); 0 ÷ 100% RH; typ.err. ±1.8% RH (10 ÷ 90% @ 25°C) | temp.: measuring range -30 ÷ 105°C; typ.err. ±0.5°C @ -10 ÷ 85°C temp. & humidity: measuring range -30 ÷ 105°C; typ.err. ±0.2°C @ 10 ÷ 60°C (±0.4°C @ -30°C, ±0.7°C @ 120°C); 0 ÷ 100% RH; typ.err. ±1.8% RH (10 ÷ 90% @ 25°C) | temp.: measuring range -50 ÷ 120°C; typ.err. ±0.5°C @ -10 ÷ 85°C temp. & humidity: measuring range -40 ÷ 120°C; typ.err. ±0.2°C @ 10 ÷ 60°C (±0.4°C @ -30°C, ±0.7°C @ 120°C); 0 ÷ 100% RH; typ.err. ±1.8% RH (10 ÷ 90% @ 25°C) | temp.: measuring range -50 ÷ 120°C; typ.err. ±0.5°C @ -10 ÷ 80°C temp. & humidity: temp. measuring range -40 ÷ 120°C; typ.err. ±0.2°C @ 10 ÷ 60°C (±0.4°C @ -30°C, ±0.7°C @ 120°C); humidity measuring range 0 ÷ 100% RH; typ.err. ±1.8% RH (10 ÷ 90% @ 25°C) | | | | |
| Connector & cable type | none | | | | | gland, cable 3m max., PUR covered, operating temp. -30 ÷ +80°C or TPE covered, operating temp. -30 ÷ +120°C | 4 pin M12 connector, cable 3m max., TPU covered, operating temp. -30 ÷ +80°C or TPE covered, operating temp. -30 ÷ +120°C | gland, cable 3m max., PUR covered, operating temp. -30 ÷ +80°C or TPE covered, operating temp. -30 ÷ +120°C | |
| Number of inputs | 1 or 2 universal | | 0 or 1 universal | | | | | | |
| Type of universal inputs | current: 0/4-20 mA; voltage: 0/1-5 V, 0/2-10V, 0-60 mV, 0-75 mV, 0-100 mV, 0-150 mV; RTD: Pt100, Pt500, Pt1000, measuring range: -100°C ÷ 600°C; thermocouple: type K, S, J, T, N, R, B, E; measuring ranges: -200°C ÷ +1370°C (K); -50°C ÷ +1768°C (S); -210°C ÷ +1200°C (J); -200°C ÷ +400°C (T); -200°C ÷ +1300°C (N); -50°C ÷ +1768°C (R); +250°C ÷ +1820°C (B); -200°C ÷ +1000°C (E) accuracy: 0.1% @ 25°C ± one digit (inputs: current, voltage, millivoltage, thermoresistance, thermocouple K, J, E); 0.2% @ 25°C (thermocouple N), 0.5% @ 25°C (thermocouple S, T, R, B) | | | | | | | | |
| Binary outputs | 0, 1 or 2 electronic NO relays, 24V AC/35V DC, max. 200 mA | | | | | | | | |
| Analogue outputs | 0, 1 or 2: active current: operating range 0/4-20 mA (0-24 mA max.); passive current: isolated, operating range 4-20 mA (2.8-24 mA max.); active voltage: operating range 0/1-5V, 0/2-10V (0-11V max.) | | | | | | | | |
| Communication interface | RS-485, 8N1 and 8N2, 1200 bit/s ÷ 115200 bit/s, Modbus RTU, not galvanically isolated | | | | | | | | |
| Operating temperature | -30°C ÷ +80°C, case with electronics (out of range -20 ÷ +70°C LCD and IR receiver turn off) | | | | | | | | |
| Protection class | IP 67 (version without display); IP 65 (version with display) | | | | | | | | |
| Case | wall mounted, 120 x 90 x 50 mm, ASA LURAN | | | | | | | | |


Data presentation




No display version, LED signalling



One measurement display mode



Two measurements display mode



Four measurements display mode



Menu display mode




Device status information

Visualisation & utility software



SimCorder Soft

SimCorder Soft communicates with external devices using the RS-485 interface with the Modbus RTU protocol and reads measurement data from the above devices. A computer may be connected directly to the network of devices or via the internet. In case of the latter, an RS-485 Ethernet converter is necessary. This software enables sound and visual alerts (e.g. in case the temperature is too high in the cooler, excessive humidity, insufficient flow etc.). The system can be configured so that each alert evokes a particular response of selected signalling modules. Any changes in the device settings as well as reading of measurements is completed remotely at one station.



Monitoring from anywhere

A computer with **SimCorder Soft** installed in the **Network SERVER** version may share recorded data and system information such as emergency states via the internet. The data can be viewed as tables or diagrams or exported to various file formats on a computer with the **Network TERMINAL** version installed. The **Network TERMINAL** version also allows to print reports based on the above data. An insight into the entire system is possible from anywhere and at any time.

Immediate notification


After detecting emergency states, **SimCorder Soft** in the Alarm or Network versions generates text messages (an external GSM modem is required) and e-mails about the same and sends them to applicable telephone numbers (max. 5 numbers) and e-mail addresses. This enables to immediately respond in case of such situations as system failure or exceeding the permissible measuring parameters.

Depends on needs there are following versions of SimCorder Software:

| Features | BASIC | ALARM | NETWORK | |
|--------------------------------------|-------|-------|---------|----------|
| | | | SERVER | TERMINAL |
| USB dongle key with license required | ✓ | ✓ | ✓ | |
| semiSCADA | ✓* | ✓* | ✓* | |
| Data measurement on demand | ✓ | ✓ | ✓ | |
| Direct cooperation with data loggers | ✓ | ✓ | ✓ | |
| Easy devices reconfiguration | ✓ | ✓ | ✓ | |
| Alarm state signalization | ✓ | ✓ | ✓ | ✓ |
| Alarm forwarding to external devices | | ✓ | ✓ | |
| GSM and e-mail notification | | ✓ | ✓ | |
| Remote network | | | ✓ | ✓ |

* functionality resulting from the license

S-Config 2



S-Config 2 software can be downloaded free from BASIS website at www.basis.se

S-Config 2 is free software used for configuring the ProSens line devices.

The software is used for a simultaneous detection of devices in multiple Modbus RTU networks and provides users with a possibility of changing the configuration of most of the devices. There is a list of registers presented for each detected device. The registers can be modified by users. The lists also include additional information concerning device parameters, such as: type, address, baud rate, etc.

The BRHT line devices can provide detailed information concerning their properties. In particular, the information includes:

- device type,
- serial number,
- firmware version,
- inputs type,
- outputs type and number.

Additional functionality available for BRHT line within the software is elaboration of personalised graphic units, displayed at measurements (e.g.: m³, l/h, kPa, °F, etc.)

Accessories



Cable probes



PPQ-612-00-X-X
Cable probe \varnothing 18, L=90 mm, w/o cable, housing SS 316L, filter FPQ-P350



PPQ-612-XX-X-X
Cable probe \varnothing 18, L=90 mm, housing SS 316L, filter FPQ-P350



PPQ-621-XX-X-X
Cable probe \varnothing 12, L=200 mm, housing SS 316L, filter from SS mesh 25 μ m



PPQ-622-XX-X-X
Cable probe \varnothing 12, L=300 mm, housing SS 316L, filter from SS mesh 25 μ m

Ordering:

PPQ-612-00-X-X

- measurement of:**
 2 : temperature
 3 : temperature & humidity

- connector type:**
 2 : connector, operating temp. $-30 \div +80^{\circ}\text{C}$
 4 : connector, operating temp. $-30 \div +120^{\circ}\text{C}$

Ordering:

PPQ-612-XX-X-X

PPQ-621-XX-X-X

PPQ-622-XX-X-X

- measurement of:**
 2 : temperature
 3 : temperature & humidity

- connector & cable type:**
 1 : gland, PUR covered, operating temp. $-30 \div +80^{\circ}\text{C}$
 3 : gland, TPE covered, operating temp. $-30 \div +120^{\circ}\text{C}$

- cable length:**
 05 (0,5m), 10 (1m), 15 (1,5m),
 20 (2m), 25 (2,5m), 30 (3m)

Filters



FPQ-P350
Teflon filter (PTFE) with increased resistance against splashing water, non-absorbent surface, does not rust, operating temperature $-30 \div +120^{\circ}\text{C}$

Mounting accessories

HPQ-FS12
Flat circular flange for \varnothing 12 probes, SS 316L



HPQ-TS12
Thread bracket for \varnothing 12 probes, SS 316L, M20x1,5



HPQ-W1218
Wall mounting bracket for \varnothing 12 and \varnothing 18 probes, SS 316L



HPQ-CGS18
Thread bracket for \varnothing 18 probes, M25x1,5



■ Accessories



■ Connection accessories



CPQ-00

M12 connector, 4-pin, w/o cable for PPQ-612 probes, operating temp. $-30 \div +80^{\circ}\text{C}$



CPX-30

M12 connector, 4-pin, cable 3 m, for PPQ-612 probes

Ordering:

CPX-30

operating temp.:

Q : standard: $-30 \div +80^{\circ}\text{C}$, cable TPU covered

T : expanded: $-30 \div +120^{\circ}\text{C}$, cable TPE covered

■ Additional accessories



SIR-15

InfraRed remote controllers may be used as external programming keyboard for BASI devices equipped with IR receivers and remote programming functions. Pressing of any local IR controller key, causes transmission of it's code to the device. Functions of particular keys depend on devices features.

Power supply voltage: 6V DC - 4 alkaline batteries type LR44

Operation range: from 0,5 to 5 m (depend on programmed device features)



SRS-U4

Module is designed to connect a USB host to slave devices equipped with RS-485 interface. The PC with special software can be used as a host. The **SRS-U4** unit guarantees full galvanic isolation between USB and RS-485 circuits. The converter can work with any devices equipped with RS-485 interface and contains integrated circuit which supports USB 1.1 and USB 2.0 standards. The main purpose is connection of PC host computer with industrial data acquisition and visualisation systems based on RS-485 interface. The **SRS-U4** can be also manufactured with DIN mounting adaptor.



SCL-QM

Case lock - access is safeguarded by means of insert lock



LSQkit

Lid supports (2 pcs)



Ordering



BRHT-XXX-XX-X-X-X-XX-X-10-3-X

probe version:

- 100-00-0 : without probe
- 211-00-0 : radial, Ø 18 mm, L=40 mm
- 212-00-0 : radial, Ø 18 mm, L=90 mm
- 213-00-0 : radial, Ø 18 mm, L=145 mm
- 421-00-0 : axial, Ø 12 mm, L=200 mm
- 422-00-0 : axial, Ø 12 mm, L=300 mm
- 621-XX-X : cable, Ø 12 mm, L=200 mm
- 622-XX-X : cable, Ø 12 mm, L=300 mm
- 612-XX-X : cable, Ø 18 mm, L=90 mm

connector & cable type:

- 1 : gland, PUR covered, operating temp. -30 ÷ +80°C
- 2 : connector, TPU covered, operating temp. -30 ÷ +80°C (applies to probe Ø 18 mm)
- 3 : gland, TPE covered, operating temp. -30 ÷ +120°C
- 4 : connector, TPE covered, operating temp. -30 ÷ +120°C (applies to probe Ø 18 mm)

cable length:

- 05 : L=0,5 m
- 10 : L=1 m
- 15 : L=1,5 m
- 20 : L=2 m
- 25 : L=2,5 m
- 30 : L=3 m

number of available glands:

- 2 : 2 pcs
- 3 : 3 pcs
- 4 : 4 pcs
- 5 : 5 pcs (does not apply to radial & axial probes)

display:

- 0 : none
- 1 : LCD, 128 x 64 pixels

outputs:

- 00 : none
- 11 : 2 x E REL
- 21 : 1 x AO (0/4-20 mA, active, non-isolated) + 1 x E REL
- 31 : 1 x AO (4-20 mA, passive, isolated) + 1 x E REL
- 41 : 1 x AO (0-10V, active, non-isolated) + 1 x E REL
- 22 : 2 x AO (0/4-20 mA, active, non-isolated)
- 33 : 2 x AO (4-20 mA, passive, isolated)
- 44 : 2 x AO (0-10V, active, non-isolated)

measurement 2:

- 0 : none
- 1 : universal input (I, U, RTD, TC)

measurement 1:

- 1 : universal input (I, U, RTD, TC) - without probe
- 2 : temperature probe
- 3 : temperature & humidity probe

Probe version:



Glands configuration:

- for ProSens 100 and 400

- for ProSens 200 and 600



3 pcs



2 pcs



BASI Instrument AB
Box 53
SE-27506 Vollsjö
Poland
tel. (+46) 40 88009
fax (+46) 40 929877
e-mail: sales@basi.se
www.basi.se



www.basi.se