

SmartSolar Charge Controllers MPPT 100/30 & 100/50

www.victronenergy.com



Bluetooth Smart built in; dongle not needed

The wireless solution to set up, monitor and update the controller using Apple and Android smartphones, tablets or other devices.

VE.Direct

For a wired data connection to a Color Control panel, Venus GX, PC or other devices.

Ultrafast Maximum Power Point Tracking (MPPT)

Especially in case of a cloudy sky, when light intensity is changing continuously, an ultra fast MPPT controller will improve energy harvest by up to 30% compared to PWM charge controllers and by up to 10% compared to slower MPPT controllers.

Advanced Maximum Power Point Detection in case of partial shading conditions

If partial shading occurs, two or more maximum power points may be present on the power voltage curve. Conventional MPPTs tend to lock to a local MPP, which may not be the optimum MPP.

The innovative BlueSolar algorithm will always maximize energy harvest by locking to the optimum MPP.

Outstanding conversion efficiency

No cooling fan. Maximum efficiency exceeds 98%.

The full output current up to 40°C (104°F).

Flexible charge algorithm

Fully programmable charge algorithm (see the software page on our website), and eight pre-programmed algorithms, selectable with a rotary switch (see manual for details).

Extensive electronic protection

Over temperature protection and power derating when temperature is high.

PV short circuit and PV reverse polarity protection.

PV reverse current protection.

Internal temperature sensor

Compensates absorption and float charge voltage for temperature.

Real time data display options

Apple and Android smartphones, tablets and other devices.
ColorControl panel.



SmartSolar Charge Controller
MPPT 100/50

SmartSolar Charge Controller	MPPT 100/30	MPPT 100/50
Battery voltage	12/24V Auto select	
Rated charge current	30A	50A
Nominal PV power, 17V (1s,1h)	440W	700W
Nominal PV power, 74V (1s,1h)	880W	1400W
Maximum PV open circuit voltage	100V	100V
Max. PV short circuit current (%)	35A	60A
Maximum efficiency	98%	98%
Self-consumption	10 mA	
Charge voltage 'absorption'	Default setting: 14,4V / 72,8V (adjustable)	
Charge voltage 'float'	Default setting: 13,8V / 77,6V (adjustable)	
Charge algorithm	Multi-stage adaptive	
Temperature compensation	-16 mV / °C, resp. -17 mV / °C	
Protection	Battery reverse polarity (fuse, not user accessible); PV reverse polarity Output short circuit Over temperature	
Operating temperature	-30 to +60°C (51° rated output up to 40°C)	
Humidity	95%, non-condensing	
Data communication port	VE.Direct See the data communication white paper on our website	
NCI COMPLIANT		
Colour	Blue (RAL 5012)	
Power terminals	13 mm ² / AWG 6	
Protection category	P43 (electronic components), IP22 (connection area)	
Weight	1,3 kg	
Dimensions (h x w x d)	130 x 186 x 70 mm	
STANDARDS		
Safety	IEC 62109-1	
1) At 11 more PV power is connected, the controller will limit input power. 1b) The PV voltage must exceed 9Vdc. = 5V for the controller to start. 1c) The minimum PV voltage is 9Vdc. = 1V. 2) A higher short circuit current may damage the controller in case of reverse polarity connection of the PV array.		