

HM750A1000

ADVANCED ELECTRODE STEAM HUMIDIFIER

SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Approval	
Service	
Tag No.	
Notes	



APPLICATION

The HM750 is the most advanced residential steam humidifier available and provides steady and reliable humidification for a home. The humidifier is designed for connection directly to a supply air duct for humidity on demand. The humidifier may be directly mounted to the air duct, or remotely from the air duct, with a steam hose connecting the humidifier to a distributor nozzle installed at the air duct.

INCLUDED IN THE BOX

- HM750 steam humidifier
- H6062 HumidiPRO
- Steam distributor nozzle
- Rubber drain hose
- LDPE water hose
- Baffle (duct mount only)
- Foam gasket (duct mount only)
- Steam hose (wall mount only)
- Fittings, hardware, and mounting template

SPECIFICATIONS	
Operating Ambient Temperature	41 to 104 °F (5 to 40 °C)
Power Supply	120 VAC or 240 VAC 50/60 Hz
Power Consumption	1.5 KW on 120 VAC 3.0 KW on 240 VAC
Amps	12 A
Phase	1
Circuit Breaker Max Current	15 A
Steam Output	on 120 VAC: 3.85 lb/hr (1.75 kg/hr) 11 GPD on 240 VAC: 7.7 lb/hr (3.5 kg/hr) 22 GPD
Max Static Pressure	2 in. w.c. positive backpressure 3 in. w.c. negative backpressure
Size length x width x depth	18 x 10 x 7 in. 457 x 254 x 178 mm
Weight	10 lbs. (15 lbs. when full) 4.5 kg. (7.0 kg. when full)

Home and Building Technologies

In the U.S.:
Honeywell
715 Peachtree Street NE
Atlanta, GA 30308
customer.honeywell.com

® U.S. Registered Trademark
© 2017 Honeywell International Inc.
33-00362-01 M.S. 11-17
Printed in United States



33-00362-01