

Print Page [SHARE](#) [f](#) [t](#) [e](#) ...[Previous](#) | Item 7 Of 8 | [Next](#)**L6006C1018/U**

High or low limit surface mount controller with SPDT, operating range 65-200F, factory stop at 200F

**Product Info****Literature****Overview**

Aquastat® Controllers are immersion type devices for limiting or regulating the temperature of liquids in boilers, storage tanks, and other applications where temperature control is required.

**Features**

- Totally enclosed Micro Switch™ snap-acting switches operate on temperature rise to set point.
- Visible control point scale and external adjustment screw permit easy setting.
- Horizontal or vertical insertion of the sensing element.
- Direct, well immersion, or surface mounting of the sensing element available.
- Remote bulb model may be used to sense air temperature in ducts and in outside air sensing applications.
- Direct or well immersion Tradeline models include heat-conductive compound.
- Select models have wells.

**Product Specifications**

Hazmat Information	UN1294 Toluene
Application	Circulator Control and High Limit or Low Limit
Dimensions (in.)	Case--5 5/8 in. high x 2 in. wide x 2 3/4 in. deep
Dimensions (mm)	Case--136 mm high x 51 mm wide x 70 mm deep
Temperature Range (F)	Maximum Ambient--150 F
Temperature Range (C)	Maximum Ambient--66 C
Includes	Stop factory-set at 200 F (93 C)
Mounting	Horizontal or Vertical or Surface mounting
Electrical Ratings	Millivolt--0.25 A @ 0.25 to 12 Vdc; At Full Load-- 8A @ 120 Vac: 5.1A @ 240 Vac; At Locked Rotor-- 48A @ 120 Vac: 30.6A @ 240 Vac
Approvals, Underwriters Laboratories Inc.	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2
Approvals, Canadian Standards Association	Certified: File No. LR95329-1
Operating Temperature Range (F)	65 F to 200 F
Operating Temperature Range (C)	18 C to 93 C
Bulb Size (in.)	3/8 in. x 2 7/8 in. copper
Bulb Size (mm)	10 mm x 73 mm copper
Differential Temperature (F)	5 F to 30 F adj.
Differential Temperature (C)	3 C to 17 C adj.
Switching Action	SPDT

**shop our product catalog**commercial products  
industrial products**support & resources**contractor pro  
literature on demand**training****helpful links**distributor locator  
commercial contractor locator

16/10/2014

High or low limit surface mount controller with SPDT, operating range 65-200F, factory stop at 200F

[residential products](#)

[feedback](#)

[residential contractor locator](#)  
[homeowners](#)

[terms & conditions](#) | [privacy statement](#) | [site map](#)

[choose region & language](#)

honeywell international inc. 2014