

On-lap 1102I Touch Monitor	
Panel	11.6" (16:9 Wide) FFS (Fringe Field Switching) panel
Active Area	256.32mm*144.18mm (WxH)
Pixel Pitch	0.1335mm (H) *0.1335mm (V)
Resolution	1920x1080
Color Depth	16.7M Colors
Brightness	250(cd/m2)(Typical)
Contrast	1000:1(Typical)
Viewing Angle	178°(H)/178°(V)(CR>10)
Surface	Anti-glare
Type of touch screen	Projective capacitive
Response Time (GTG)	12.5(ms)(Typical)
Video Input	HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1
HDCP Support	Yes
Plug & Play	VESA DDC2B/C1
Audio Output	Headphone Out
Power On(Max.)	?8W
Standby Mode	<0.5W
Power Off Mode	<0.5W
Rating power	5V---1.7A
Connectivity	HDMI*2(Micro HDMI port*1,Rear dock port*1),VGA*1 3.5mm mini jack 5V DC*1 (Micro USB)
Environment	Operating :0~50?;Humidity:20~90%RH Storage:-20~60?;Humidity:10~90%RH
Cabinet Colors	Front: Black Rear: Gunmetal grey Cover: Black
Dimension	294mm*194mm*12mm(Monitor) 299mm*209mm*21mm(Monitor and cover)
Net Weight	670g(Monitor) 920g(Monitor and cover)

Accessories in package	Cover Stand*1; HDMI-A to micro-HDMI cable 1.2m*1 USB-A to micro-USB cable 1.2m*1 5V-2A adapter*1
Certification	BSMI, CE, FCC,RCM, VCCI,KC and RoHS
Warranty	1 year limited