ALLURE E+ 0

SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
ACCU	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	XS, S, M, L
KLEUREN	Storm Cloud
FRAME	ALUXX aluminum, Overdrive 1½ - 1⅛" head tube, integrated KSA40 kickstand mount
VOORVORK	SR Suntour Mobie 25 LO DS air 700c 63mm travel 15x100 AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm
HANDVATTEN	Liv Comfort Ergo Microtech Plus
STUURPEN	Aluminum angle adjustable stem
ZADELPEN	Dropper seat-post
ZADEL	Selle Royal Lift
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Enviolo Automatiq integrated
ACHTERDERAILLEUR	-
REMMEN	Shimano Deore, BR-MT420, hydraulic disc, 4-piston, 180mm [F/R]
REMHENDELS	Shimano BR-MT420
CASSETTE	Gates CDC stainless steel 22T rear sprocket
AANDRIJVING	Gates CDC Carbon Drive 122T CenterTrack belt
CRANKSET	Gates CDC CenterTrack 46T front sprocket

WIELSET	
VELGEN	Liv GX03V 700c aluminium
NAVEN	Giant eTracker 6-bolt disc 15x100mm [F], Enviolo Automatiq 6-bolt disc solid axle [R]
SPAKEN	Stainless steel
BANDEN	Schwalbe Marathon E Plus 622x55, Smart DualGuard Addix E
EXTRA'S	Aegis Tire Checker
ACCESSORES	
VERLICHTING	Supernova mini 2 LDM [F] Carrier integrated light [R]
SLOT	ABUS Xplus battery lock Granit Xplus ART 6950ML R frame lock
DRAGER	MIK rack. System child set, bag & basket, Aegis Radar spec-in

Adviesprijs: € 4.799,00

GEOMETRIE

FRAME	S	M	L
Zitbuis Lengte (mm)	430	460	495
Zitbuis Hoek	73,5°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	580	600	620
Balhoofdbuis Lengte (mm)	180	200	200
Balhoofdbuis Hoek	69,5°	69,5°	69,5°
Vork Sprong (mm)	46	46	46
Naloop (mm)	94,5	94,5	94,5
Wielbasis (mm)	1137	1152	1165
Liggende achtervork lengte (mm)	482	482	482
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	662	681	681
Reach (mm)	384	392	405
Stand Over Height (mm)	428	431	437
Stuur breedte (mm)	660	660	660
Stuurpen Lengte (mm)	80	80	100
Cranklengte (mm)	165	170	170
Wielmaat	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.