



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Moonstone/Gray/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
HANDVATTEN	Liv Stratus Elite 2.0
STUURPEN	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ZADEL	Liv Approach
AFMONTAGE	
SHIFTERS	Shimano 105
VOORDERAILLEUR	Shimano 105
ACHTERDERAILLEUR	Shimano 105
REMMEN	Shimano 105 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
AANDRIJVING	KMC 12
CRANKSET	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant P-R1 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Gavia Fondo 1, tubeless, 700x32c, folding
EXTRA'S	two bottle cage, fender mount, tubeless prepared, 40mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	40mm

Adviesprijs: € 2.799,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	405	435	465	495
Zitbuis Hoek	74,5°	74,5°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	520	525	535	550
Balhoofdbuis Lengte (mm)	125	145	165	185
Balhoofdbuis Hoek	71,0°	71,0°	71,0°	72,0°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	68,3	68,3	68,3	61,8
Wielbasis (mm)	995	1002	1007	1013
Liggende achtervork lengte (mm)	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	75
Stack (mm)	528	547	566	589
Reach (mm)	373	373	373	381
Stand Over Height (mm)	712	737	762	789
Stuur breedte (mm)	380	400	400	420
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	165	170	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.