



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Lavender Blush
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Connect, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Sport, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
ZADELPEN	Giant D-Fuse, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ZADEL	Liv Approach
AFMONTAGE	
SHIFTERS	Shimano CUES U6030
VOORDERAILLEUR	Shimano CUES U6030F
ACHTERDERAILLEUR	Shimano CUES U6020-10
REMMEN	Shimano BR-U6030 hydraulic, Giant MPH rotors, [F] 160mm, [R] 160mm
REMHENDELS	Shimano CUES U6030
CASSETTE	Shimano CS-LG400, 10-speed, 11x39
AANDRIJVING	KMC X11
CRANKSET	Shimano FC-U6030-2, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano BB-RS501

WIELSET	
VELGEN	Giant S-R2 Disc
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless
BANDEN	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRA'S	tubeless prepared, 38mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	38mm

Adviesprijs: € 1.499,00

## GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	430	465	500	535
Zitbuis Hoek	75,0°	74,5°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	515	525	540	555
Balhoofdbuis Lengte (mm)	135	150	170	190
Balhoofdbuis Hoek	70,5°	72,0°	72,0°	72,0°
Vork Sprong (mm)	45	45	45	45
Naloop (mm)	73	63,5	63,5	63,5
Wielbasis (mm)	998	990	1000	1016
Liggende achtervork lengte (mm)	420	420	420	420
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	530	550	569	588
Reach (mm)	372	372	377	386
Stand Over Height (mm)	687	716	744	772
Stuur breedte (mm)	380	400	400	420
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	165	170	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.