



NOTES:

1. DESCRIPTION: R.F. SCREENED DESICCATOR 20, 30, 40P
2. DESICCATOR IS MADE FROM ALUMINIUM ALLOY, FINISH ANODISE TO DEF STAN 03-25 AND DYE BLACK EXCEPT FOR THREADS WHICH ARE CONDUCTIVE TO ALLOW FOR RF SCREENING CONTINUITY / EMC SHIELDING.
3. HUMIDITY INDICATOR RESPONDS TO 20, 30, & 40% RELATIVE HUMIDITY (RH) - A BLUE COLOUR IN SEGMENTS INDICATES RELATIVE HUMIDITY IS LOWER THAN SPECIFIED VALUES ON CARD. LAVENDER OR PINK COLOUR IN SEGMENT INDICATES RH IS EQUAL OR GREATER THAN THE NUMBER IN THAT SEGMENT. COLOUR INDICATION OF CARD IS FULLY REVERSIBLE.
4. DESICCANT: SILICA GEL, 1-3 MM BEADS, APPROX. 1 GRAM

REVISION		DATE		TITLE	
REVISED	A. QUENT	9-16-2000	DRYTRADE NORDIC AB		
	C. LEHT	9-16-2000	STATIC DESICCATOR		
			R.F. SCREENED		
TOLERANCES		SIZE	DRWG NO		
LINEAR	±0.4	ANGULAR	A3	DESS234F	1
			SCALE	NONE	SHEET 1 OF 1