

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

GI 112 A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

sealant

Uses advised against

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Manufacturer

| | | |
|-------------------------|---|---------------------------------|
| Company name: | Gremmler Bauchemie GmbH | |
| Street: | Lise-Meitner-Straße 5 | |
| Place: | D-46569 Hünxe | |
| Telephone: | +49 (0) 281/ 94403 - 40 | Telefax: +49 (0) 281/94403 - 44 |
| Internet: | http://www.gremmler.de | |
| Responsible Department: | Technical Department | |
| | msds@gremmler.de | |

Supplier

| | |
|-----------------|--|
| Company name: | EG Floor ApS |
| Street: | Stensmosevej 24M |
| Place: | DK- 2620 Albertslund |
| Contact person: | Rasmus Lyng |
| e-mail: | Info@egfloor.dk |

1.4. Emergency telephone number:

Gifflinjen - DK +45 82121212

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)

Bisphenol F-epoxy resin

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Signal word: Warning

Safety Data Sheet


according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 2 of 11

Pictograms:



Hazard statements

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|-----------|--|
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |

Special labelling of certain mixtures

| | |
|--------|---|
| EUH205 | Contains epoxy constituents. May produce an allergic reaction. Restricted to professional users. |
|--------|---|

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

formulated epoxy resin.

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|--|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | | | 60 - < 65 % |
| | 500-033-5 | 603-074-00-8 | 01-2119456619-26 | |
| | Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411 | | | |
| 9003-36-5 | Bisphenol F-epoxy resin | | | 20 - < 25 % |
| | 500-006-8 | | 01-2119454392-40 | |
| | Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411 | | | |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | | | 15 - < 20 % |
| | 271-846-8 | 603-103-00-4 | 01-2119485289-22 | |
| | Skin Irrit. 2, Skin Sens. 1; H315 H317 | | | |

Full text of H and EUH statements: see section 16.

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. In

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 3 of 11

case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO₂). Foam. Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 4 of 11

7.1. Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Usual measures for fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

Hints on joint storage

For more information about together and separate storage: refer to TRGS 510

Further information on storage conditions

Recommended storage temperature: 5 - 30 °C

Keep/Store only in original container.

Store in a dry place.

7.3. Specific end use(s)

Further remarks:

Information System of the Professional Association of construction industry see on www.gisbau.de

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|------------------------|--|----------------|----------|-------------------------|
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | | | |
| Worker DNEL, long-term | | inhalation | systemic | 12,25 mg/m ³ |
| Worker DNEL, acute | | inhalation | systemic | 12,25 mg/m ³ |
| Worker DNEL, long-term | | dermal | systemic | 8,33 mg/kg bw/day |
| Worker DNEL, acute | | dermal | systemic | 8,33 mg/kg bw/day |
| 9003-36-5 | Bisphenol F-epoxy resin | | | |
| Worker DNEL, long-term | | dermal | systemic | 104,15 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 29,39 mg/m ³ |
| 68609-97-2 | oxirane, mono[[C12-14-alkyloxy)methyl] derivs. | | | |
| Worker DNEL, long-term | | dermal | systemic | 1,0 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 3,6 mg/m ³ |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 5 of 11

PNEC values

| CAS No | Substance | |
|------------|--|--------------|
| | Environmental compartment | Value |
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | |
| | Freshwater | 0,006 mg/l |
| | Marine water | 0,001 mg/l |
| | Freshwater sediment | 0,996 mg/kg |
| | Marine sediment | 0,1 mg/kg |
| | Soil | 0,196 mg/kg |
| 9003-36-5 | Bisphenol F-epoxy resin | |
| | Freshwater | 0,003 mg/l |
| | Marine water | 0,000 mg/l |
| | Freshwater sediment | 0,294 mg/kg |
| | Marine sediment | 0,029 mg/kg |
| | Soil | 0,237 mg/kg |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | |
| | Freshwater | 0,106 mg/l |
| | Marine water | 0,01 mg/l |
| | Freshwater sediment | 307,16 mg/kg |
| | Marine sediment | 30,72 mg/kg |
| | Soil | 1,234 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommendation to EN 374: For short time use or protection against splashes: Butyl rubber / nitrile rubber (0.4 mm), contaminated gloves should be changed and disposed. Suitable for permanent exposure: Viton gloves (0.4 mm) Break through time > 30 min.

Skin protection

Wear suitable protective clothing. Recommendation: Safety shoes according to EN ISO 20345, long pants and long-sleeved work shirt; with mixing and stirring work additional rubber apron and protective boots according to EN 14605

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: transparent
 Odour: slightly.

Test method

pH-Value: No information available.

Flash point: >93 °C calculated.

Explosive properties

No information available.

Ignition temperature: No information available.

Decomposition temperature: No information available.

Oxidizing properties

No information available.

Vapour pressure: No information available.

Density (at 23 °C): ca. 1,11 g/cm³ ISO 2811-2

Water solubility: No information available.

Solubility in other solvents

No information available.

Partition coefficient: No information available.

Viscosity / dynamic:
 (at 25 °C) 570 - 850 mPa·s ISO 2884-1

Vapour density: No information available.

Evaporation rate: No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 7 of 11

| CAS No | Chemical name | | | | |
|------------|--|-------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | | | | |
| | oral | LD50 >5000 mg/kg | Rat | | |
| | dermal | LD50 >2000 mg/kg | Rat | | |
| 9003-36-5 | Bisphenol F-epoxy resin | | | | |
| | oral | LD50 >10000 mg/kg | Rat | | |
| | dermal | LD50 >2000 mg/kg | Rat | | |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | | | | |
| | oral | LD50 >10000 mg/kg | Rat | | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin); Bisphenol F-epoxy resin; oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

| CAS No | Chemical name | | | | | |
|------------|--|----------------|-----------|--|--------------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | | | | | |
| | Acute fish toxicity | LC50 1,5 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) (OECD 203) | ECHA Dossier | |
| 9003-36-5 | Bisphenol F-epoxy resin | | | | | |
| | Acute fish toxicity | LC50 2,54 mg/l | 96 h | Leuciscus idus (golden orfe) | | |
| | Acute algae toxicity | ErC50 1,8 mg/l | 72 h | algae. | | |
| | Acute crustacea toxicity | EC50 2,55 mg/l | 48 h | Daphnia magna (Big water flea) | | |

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 8 of 11

| CAS No | Chemical name | | | |
|------------|--|-------|----|--------------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | | | |
| | OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D | 5% | 28 | ECHA Dossier |
| | Not easily bio-degradable (according to OECD-criteria). | | | |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | | | |
| | OECD 301 F | 87% | 28 | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|--|---------|
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | 3,8 |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | >3 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|--|----------|---------|--------|
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 100-3000 | | |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 9 of 11

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|--|
| 14.1. UN number: | UN 3082 |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) |
| 14.3. Transport hazard class(es): | 9 |
| 14.4. Packing group: | III |
| Hazard label: | 9 |
| Classification code: | M6 |
| Special Provisions: | 274 335 375 601 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 90 |
| Tunnel restriction code: | - |

Marine transport (IMDG)

| | |
|--|--|
| 14.1. UN number: | UN 3082 |
| 14.2. UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) |
| 14.3. Transport hazard class(es): | 9 |
| 14.4. Packing group: | III |
| Hazard label: | 9 |
| Marine pollutant: | Yes |
| Special Provisions: | 274, 335, 969 |
| Limited quantity: | 5 L |
| Excepted quantity: | E1 |
| EmS: | F-A, S-F |

14.5. Environmental hazards

| | |
|-----------------------------|-------------|
| ENVIRONMENTALLY HAZARDOUS: | yes |
| Danger releasing substance: | epoxy resin |

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

| | |
|---|---|
| 2004/42/EC (VOC): | VOC content (g/L), delivery state: < 500 |
| Subcategory according to Directive 2004/42/EC: | Two-pack reactive performance coatings for specific end use such as floors - Solvent-borne coatings, VOC limit value: 500 g/l |
| Information according to 2012/18/EU (SEVESO III): | E2 Hazardous to the Aquatic Environment |

Additional information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 10 of 11

Prohibition/Restriction:

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). None of the components are listed (\Rightarrow 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV): not applicable

REACH Information: All substances contained in our Products are preregistered or registered by our upstream suppliers, and/or preregistered or registered by us, and/or excluded from the regulation, and/or exempted from the registration.

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)
Bisphenol F-epoxy resin
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Skin Irrit. 2; H315 | Calculation method |
| Eye Irrit. 2; H319 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| Aquatic Chronic 2; H411 | Calculation method |

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

GI 112 A

Revision date: 21.01.2019

Page 11 of 11

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)