

High flexible flat braided copper tape

Article no.		Technical data				
Uncoated	Tinned	Area mm ²	Dimensions mm			Weight kg/100m
			Thread diam.	No. of threads	Width x thickness	
CUBLFL 1	CUFÖFL 1	1	0,05	16 x 32	3,2 x 0,7	1,50
CUBLFL 1,5	CUFÖFL 1,5	1,5	0,07	16 x 25	4 x 1	1,70
CUBLFL 2	CUFÖFL 2	2	0,07	16 x 33	5 x 0,8	2,20
CUBLFL 2,5	CUFÖFL 2,5	2,5	0,07	24 x 27	5,8 x 1	2,70
CUBLFL 4	CUFÖFL 4	4	0,07	24 x 43	8,2 x 1	4,25
CUBLFL 6	CUFÖFL 6	6	0,07	24 x 66	10 x 1	6
CUBLFL 8	CUFÖFL 8	8	0,07	24 x 88	12 x 1,1	8
CUBLFL 10	CUFÖFL 10	10	0,07	24 x 109	13,8 x 1,3	10
CUBLFL 16	CUFÖFL 16	16	0,10	24 x 85	18 x 2	16
CUBLFL 25	CUFÖFL 25	25	0,10	24 x 135	20 x 2,4	25
CUBLFL 35	CUFÖFL 35	35	0,10	32 x 139	26 x 2,3	35
CUBLFL 50	CUFÖFL 50	50	0,10	48 x 133	33 x 2,8	50
CUBLFL 70	CUFÖFL 70	70	0,10	48 x 186	38 x 3	70
CUBLFL 95	CUFÖFL 95	95	0,10	48 x 256	45 x 4,5	95
CUBLFL120	CUFÖFL120	120	0,10	48 x 320	50 x 4,5	120
CUBLFL140	CUFÖFL140	140	0,10	48 x 373	55 x 5,3	140
CUBLFL150	CUFÖFL150	150	0,1	48 x 399	65 x 5	150
CUBLFL168	CUFÖFL168	168	0,10	48 x 446	70 x 4,5	168
CUBLFL185	CUFÖFL185	185	0,1	48 x 491	75 x 5	185
CUBLFL240	CUFÖFL240	240	0,10	48 x 637	80 x 6,5	240
CUBLFL300	CUFÖFL300	300	0,10	48 x 797	90 x 7	300
CUBLFL400	CUFÖFL400	400	0,10	48 x 1062	100 x 8,5	400

Technical data

Material

Annealed Cu-ETP
uncoated or tinned
version

Supplied by meter or as
customized connections

Produced according to
DIN EN 13602

Other areas and
dimensions upon request

