Stûv 21 – 105 SF

Fitted device or open fire without a hot water supply complying with the EN 13229: 2001 / A2: 2004 standard Recommended fuel: wooden logs only

Manufactured by:

Stûv s.a

Rue Jules Borbouse, 4 B-5170 Bois-de-Villers Tel.: +32(0)81.43.47.96 - Fax: +32(0)81.43.48.74 info@stuv.com www.stuv.com

Approved certifying body:

2013 – Laboratory KVBV – ARGB Rodestraat 125 B-1630 Linkebeek

System to assess and check the consistency of performance: 3 Test report number: 10101/1 Document number: 10 QA 101322907-EN

European standards	EN	13229:2001/A2:2004/AC:2007
Main features		Performance
CO emissions		0,09 %
Smoke temperature at nominal power		242 °C
Heating power	Nominal:	19 kW
	Distributed in the room:	19 kW
	Distributed in water:	– kW
Output		84 %
Maximum water pressure when operating		-
Surface temperature		Pass
Surface temperature		Pass
Electrical safety		Pass
Mechanical resistance (for the pipe to withstand)		NPD
Fire safety		
Reaction to fire		A1
Minimum distances in relation	Rear insulation thickness	140 mm
to combustible materials	Side insulation thickness	150 mm
	Top insulation thickness	180 mm
	Front insulation thickness	800 mm
	Insulation thickness in relation to	the floor 10 mm
Fire risk after burning fuel has fallen		Pass

Bois-de-Villers, 2014

Gérard Pitance

Chief Executive and Founder





STÛV

Managing Director and Chief Executive