

Stuv 21 – 125 DF

Fitted device or open fire without a hot water supply
complying with the EN 13229: 2001 / A2: 2004 standard
Recommended fuel: wooden logs only

Manufactured by:

Stuv s.a

Rue Jules Borbouse, 4 B-5170 Bois-de-Villers
Tel.: +32(0)81.43.47.96 – Fax: +32(0)81.43.48.74
info@stuv.com www.stuv.com

Approved certifying body:

0608 – SGS Nederland bv
Leemansweg 51 NL-6827 BX Amhem

System to assess and check the consistency of performance: 3
Test report number: EZ/06/1989/03
Document number: 07.QA.071322904-EN

This device complies with CE regulations



European standards	EN 13229:2001/A2:2004/AC:2007	
Main features	Performance	
CO emissions	0,21 %	
Smoke temperature at nominal power	251 °C	
Heating power	Nominal:	27 kW
	Distributed in the room:	27 kW
	Distributed in water:	- kW
Output	72 %	
Maximum water pressure when operating	-	
Surface temperature	Pass	
Surface temperature	Pass	
Electrical safety	Pass	
Mechanical resistance (for the pipe to withstand)	NPD	
Fire safety		
Reaction to fire	A1	
Minimum distances in relation to combustible materials	Rear insulation thickness	- mm
	Side insulation thickness	130 mm
	Top insulation thickness	130 mm
	Front insulation thickness	800 mm
	Insulation thickness in relation to the floor	10 mm
Fire risk after burning fuel has fallen	Pass	

Bois-de-Villers, 2014

Gérard Pitance

Chief Executive and Founder

Jean-François Sidler

Managing Director and Chief Executive