Declaration of performance EU 305/2011



Stûv 21 - 75 DF

Fitted device or open fire without a hot water supply complying with the EN 13229: 2001 / A2: 2004 standard Recommended fuel: wooden logs only

Manufactured by:

Stûv s.a

Rue Jules Borbouse, 4 B-5170 Bois-de-Villers Tel.: +32(0)81.43.47.96 - Fax: +32(0)81.43.48.74

info@stuv.com www.stuv.com

Approved certifying body:

0608 - SGS Nederland by

Leemansweg 51 NL-6827 BX Amhem

System to assess and check the consistency of performance: 3

Test report number: EZKA/12/092-1 Document number: 12 QA 121322912-EN



European standards	EN	N 13229:2001/A2:2004/AC:2007
Main features		Performance
CO emissions		0,08 %
Smoke temperature at nominal power		344 °C
Heating power	Nominal:	19 kW
	Distributed in the room:	19 kW
	Distributed in water:	- kW
Output		75 %
Maximum water pressure when operating		-
Surface temperature		Pass
Surface temperature		Pass
Electrical safety		Pass
Mechanical resistance (for the pipe to withstand)		NPD
Fire safety		
Reaction to fire		A1
Minimum distances in relation	Rear insulation thickness	- mm
to combustible materials	Side insulation thickness	150 mm
	Top insulation thickness	110 mm
	Front insulation thickness	800 mm
	Insulation thickness in relation to	the floor 0 mm
Fire risk after burning fuel has fallen		Pass

Bois-de-Villers, 2014

Gérard Pitance

Jean-François Sidler

Chief Executive and Founder

Managing Director and Chief Executive