



metalfire

| architectural fireplaces |

**model** URBAN MF 1050-600-50 G 3S EXT  
(BASIC VERSION)

**Dimensions (mm)**

- combustion chamber WxDxH 960 x 420 x 500
- combustion chamber at finish size WxDxH 1050 x 600 x 490
- length of burner 800
- external WxDxH 1233 x 600 x 1675
- fresh air 2 x  $\varnothing 150$

**Technical Data (city gas)**

for other types of gas see 'gasburner specifications' (options)

- appliance type B11AS/B14AS
- load 19,53 kW
- type of gas/pressure G20/20,25/25mBar
- gascat. I2E+, I2H, I2E, I2L

**Protection**

- 'oxy-pilot'-protection
- ionization-protected pilot-flame
- secured flue pipe discharge
- secured oxygen supply

**Specifications**

- control unit on the side
- finishing: heat-resistant black paint
- lockable valve for fresh air and smoke gases
- remote control with electronic ignition

**Options**

- chimney fan RSVG 250 or 315: type depending on situation for further info contact the Metalfire dealer
- convection jacket (see options)

scale 1:20

www.metalfire.eu

EN 509 CE

General dimensional tolerances up to 6mm  
Metalfire preserves the right to modify specifications without previous notice