

# metalfire

| architectural fireplaces |

**model** URBAN MF 1900-40 G T

**Dimensions (mm)**

- combustion chamber WxDxH 1900 x 600 x 400
- length of burner 1600
- external WxDxH 2166 x 600 x 1675
- fresh air 2 x Ø150

**Technical Data (city gas)**

for other types of gas see 'gasburner specifications' (options)

- appliance type B11AS/B14AS
- load 21,93 kW
- type of gas/pressure G20/20,25/25mBar
- gascat. I2E+, I2H, I2E, I2L
- weight +/-214kg

**Protection**

- 'oxy-pilot'-protection
- ionization-protected pilot-flame
- secured flue pipe discharge
- secured oxygen supply

**Specifications**


- control unit on the right
- finishing: heat-resistant black paint
- lockable valve for fresh air and smoke gases
- grey pebbles
- remote control with electronic ignition
- one side closed with fixed glass panel

**Options**

- chimney fan RSVG 250
- sides combustion chamber finishing:
  - ribbed cast-iron
  - ceramic woodlogs
  - convection jacket (see options)

scale 1:20

[www.metalfire.eu](http://www.metalfire.eu)

EN 509 

General dimensional tolerances up to 6mm  
Metalfire preserves the right to modify specifications without previous notice

