

Stuv 16/58 – UP

Domestic heater using solid fuel without a hot water supply
complying with the EN 13240: 2001 / A2: 2004 standard
Recommended fuel: wooden logs only

Manufactured by:

Stuv s.a

Rue Jules Borbouse, 4 B-5170 Bois-de-Villers
Tel.: +32(0)81.43.47.96 – Fax: +32(0)81.43.48.74
info@stuv.com www.stuv.com

Approved certifying body:

0608 – SGS Nederland bv
Leemansweg 51 NL-6827 BX Amhem

System to assess and check the consistency of performance: 3
Test report number: EZKA/2016-07/00018-3
Document number: 10 QA 101324006-EN

This device complies with CE regulations



| | | | |
|--|---|----------------------|--|
| European standards | EN 13240:2001/A2:2004/AC:2007 | | |
| Main features | Performance | | |
| CO emissions | 0,09 % | | |
| Smoke temperature at nominal power | 283 °C | | |
| Heating power | Nominal: | 7 kW | |
| | Distributed in the room: | 7 kW | |
| | Distributed in water: | – kW | |
| Output | 78 % | | |
| Maximum water pressure when operating | – | | |
| Surface temperature | Pass | | |
| Cleaning capacity | Pass | | |
| Electrical safety | Pass | | |
| Mechanical resistance (for the pipe to withstand) | NPD | | |
| Fire safety | | | |
| Reaction to fire | A1 | | |
| Minimum distances in relation to combustible materials | Minimum distance to the rear | Non-combustible wall | |
| | Minimum distance to the side | 250 mm | |
| | Minimum distance above | – mm | |
| | Minimum distance to the front | 1500 mm | |
| | Minimum distance in relation to the floor | 0 mm | |
| Fire risk after the fall of burning fuel | Pass | | |

Bois-de-Villers, 2017

Gérard Pitance

Chief Executive and Founder

Jean-François Sidler

Managing Director and Chief Executive