Technical parameters

Model(s):	**CGK050V4P**
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with supplementary heater:	NO
Heat pump combination heater:	NO

Average climate - low -temperature application
平均气候-低温应用

Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heat output 额定输出功率	*Prated*	10.399	kW		Seasonal space heating energy efficiency 季节性空间供暖 能源效率	η_s	184.6	%
声明的在 20℃ 室内温度和室外温度下部分负荷的加热能力 Declared capacity for heating for part load at indoor temperature 20 ℃ and outdoor temperature T_j					室内温度 20℃ 和室外温度下部分负荷的声明性能系数或一次能源比 Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 ℃ and outdoor temperature T_j			
T_j = -7 ℃	*Pdh*	9.199	kW		T_j = -7 ℃	*COPd*	2.73	%
T_j = +2 ℃	*Pdh*	5.648	kW		T_j = +2 ℃	*COPd*	4.80	%
T_j = +7 ℃	*Pdh*	5.831	kW		T_j = +7 ℃	*COPd*	6.51	%
T_j = +12 ℃	*Pdh*	6.702	kW		T_j = +12 ℃	*COPd*	8.45	%
T_j = bivalent temperature 二价温度	*Pdh*	9.199	kW		T_j = bivalent temperature 二价温度	*COPd*	2.73	%
T_j = operation limit temperature 工作极限温度	*Pdh*	9.541	kW		T_j = operation limit temperature 工作极限温度	*COPd*	2.46	%
T_j = -15 ℃	*Pdh*	-	kW		T_j = -15 ℃	*Pdh*	-	kW
Bivalent temperature 二价温度	T_{biv}	-7	℃		Operation limit temperature (for air-to-water heat pumps)工作极限温度	*TOL*	-10	℃
Cycling interval capacity for heating 循环间隔加热能力	*Pcych*	-	kW		Cycling interval efficiency 循环间隔效率	*COPcyc*	-	%
Degradation coefficient 降解系数	*Cdh*	0.90	-		Heating water operating limit temperature 热水运行极限温度	*WTOL*	60	℃
Power consumption in modes other than active mode 非活动模式下的功耗					Supplementary heater 辅助加热器			
Off mode 关模式	P_{OFF}	0.015	kW		Rated heat output 额定输出功率	*Psup*	0.858	kW
Thermostat-off mode 恒温器关闭模式	P_{TO}	0.025	kW		Type of energy input 能量输入类型	resistive 抵抗的		
Standby mode 待机模式	P_{SB}	0.015	kW					
Crankcase heater mode 曲轴箱加热器模式	P_{CK}	0.038	kW					
Other item 其他项目								
Capacity control 容量控制	fixed 固定				Rated air flow rate, outdoors (for air-to-water heat pumps) 室外额定空气流量（用于空气对水热泵）	-	5000	m^3/h

Sound power level, indoors / outdoors 声功率级室内/室外	L_{WA}	54	dB					
Annual energy consumption 年度能耗	Q_{HE}	4582	kWh		Rated brine or water flow rate, outdoor heat exchanger (for water- or brine-to-water heat pumps)	-	-	m^3/h

Technical parameters

Model(s):	**CGK050V4P**
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with supplementary heater:	NO
Heat pump combination heater:	NO

Average climate -medium-temperature application
平均气候-中温应用

Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heat output 额定输出功率	*Prated*	9.330	kW		Seasonal space heating energy efficiency 季节性空间供暖 能源效率	η_s	141.8	%
声明的在 20°C 室内温度和室外温度下部分负荷的加热能力 Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j					室内温度 20°C 和室外温度下部分负荷的声明性能系数或一次能源比 Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j = -7 °C	*Pdh*	8.254	kW		T_j = -7 °C	*COPd*	2.30	%
T_j = +2 °C	*Pdh*	5.321	kW		T_j = +2 °C	*COPd*	3.64	%
T_j = +7 °C	*Pdh*	5.459	kW		T_j = +7 °C	*COPd*	4.90	%
T_j = +12 °C	*Pdh*	6.330	kW		T_j = +12 °C	*COPd*	6.38	%
T_j = bivalent temperature 二价温度	*Pdh*	8.254	kW		T_j = bivalent temperature 二价温度	*COPd*	2.30	%
T_j = operation limit temperature 工作极限温度	*Pdh*	9.147	kW		T_j = operation limit temperature 工作极限温度	*COPd*	2.07	%
T_j = -15 °C	*Pdh*	-	kW		T_j = -15 °C	*Pdh*	-	kW
Bivalent temperature 二价温度	T_{biv}	-7	°C		Operation limit temperature (for air-to-water heat pumps)工作极限温度	*TOL*	-10	°C
Cycling interval capacity for heating 循环间隔加热能力	*Pcych*	-	kW		Cycling interval efficiency 循环间隔效率	*COPcyc*	-	%
Degradation coefficient 降解系数	*Cdh*	0.90	-		Heating water operating limit temperature 热水运行极限温度	*WTOL*	60	°C
Power consumption in modes other than active mode 非活动模式下的功耗					Supplementary heater 辅助加热器			
Off mode 关模式	P_{OFF}	0.015	kW		Rated heat output 额定输出功率	*Psup*	0.183	kW
Thermostat-off mode 恒温器关闭模式	P_{TO}	0.025	kW		Type of energy input 能量输入类型	resistive 抵抗的		
Standby mode 待机模式	P_{SB}	0.015	kW					
Crankcase heater mode 曲轴箱加热器模式	P_{CK}	0.038	kW					
Other item 其他项目								
Capacity control 容量控制	fixed 固定				Rated air flow rate, outdoors			

Sound power level, indoors / outdoors 声功率级室内/室外	L_{WA}	54	dB		(for air-to-water heat pumps) 室外额定空气流量（用于空气对水热泵）	-	5000	m^3/h
Annual energy consumption 年度能耗	Q_{HE}	5327	kWh		Rated brine or water flow rate, outdoor heat exchanger (for water- or brine-to-water heat pumps)	-	-	m^3/h