

ECO DELTA 9BB Mono Big Cell(166) Half-cut Cell PV Module
ECO-355-375M-60EHC



Higher Module Efficiency
Brings 0-+3W Power gain due to half-cut production system



INNOVATIONAL 166 HALF-CELL TECHNOLOGY
Improves the module output, decreases the risk of mirco-crack, enhances the module reliability.



INNOVATIVE PERC CELL TECHNOLOGY
Excellent cell efficiency and output.



REDUCE SHADOW LOSS
Effectively reduces the effect of shadow on the module surface.




REDUCE INTERNAL MISMATCH LOSS
Reduces mismatch loss and improves output.




PASSED HAIL TEST
Certified to hail resistance: ice ball size (d=45mm) and ice ball velocity (v=30.7m/s).



PID RESISTANCE
Excellent PID resistance at 96 hours (@85°C/85%) test, and also can be improved to meet higher standards for the particularly harsh environment



LINEAR PERFORMANCE WARRANTY



QUALITY WARRANTY

Eco Delta guarantees that defects will not appear in materials and workmanship defined by IEC61215 or IEC61730 under normal installation, use and maintenance as specified in Eco Delta's installation manual for 12 years from the warranty starting date.

ISO9001
ISO14001
OHSAS18001



About Eco Delta

Eco Delta Power Co.,Ltd specializes in research, development, production, and sales of solar PV products as well as provision of related services and provides customers around the world with high-quality PV products.

www.ecodeltapower.com

ECO DELTA 9BB Mono Big Cell(166) Half-cut Cell PV Module

ECO-355-375M-60EHC



| ELECTRICAL DATA @ STC | | ECO-355M-60 EHC | ECO-360M-60 EHC | ECO-365M-60 EHC | ECO-370M-60 EHC | ECO-375M-60 EHC |
|-----------------------------|-----|-----------------|-----------------|-----------------|-----------------|-----------------|
| Peak Power(Pmax) | (W) | 355 | 360 | 365 | 370 | 375 |
| Maximum Power Voltage (Vmp) | (V) | 33.36 | 33.61 | 33.86 | 34.07 | 34.34 |
| Maximum Power Current(Imp) | (A) | 10.64 | 10.71 | 10.78 | 10.86 | 10.92 |
| Open-circuit Voltage (Voc) | (V) | 39.80 | 40.10 | 40.38 | 40.66 | 40.93 |
| Short-circuit Current(Isc) | (A) | 11.13 | 11.20 | 11.26 | 11.34 | 11.40 |
| Module Efficiency | (%) | 19.20 | 19.50 | 19.70 | 20.00 | 20.30 |
| Operating Temperature | | -40°C~+85°C | | | | |
| Maximum System Voltage | | □ 1000V □ 1500V | | | | |
| Maximum Series Fuse Rating | | 15A | | | | |
| Power Telorance | | 0~+3% | | | | |

*STC (Standard Test Condition): Irradiance 1000W/ ㎡ , Module Temperature 25°C, AM 1.5

| ELECTRICAL DATA @ NMOT | | ECO-355M-60 EHC | ECO-360M-60 EHC | ECO-365M-60 EHC | ECO-370M-60 EHC | ECO-375M-60 EHC |
|----------------------------|-----|-----------------|-----------------|-----------------|-----------------|-----------------|
| Peak Power(Pmax) | (W) | 265 | 269 | 272 | 276 | 280 |
| MPP Voltage (Vmp) | (V) | 31.11 | 31.34 | 31.57 | 31.76 | 32.02 |
| MPP Current(Imp) | (A) | 8.51 | 8.58 | 8.62 | 8.69 | 8.73 |
| Open Circuit Voltage (Voc) | (V) | 37.42 | 37.70 | 37.96 | 38.23 | 38.48 |
| Short Circuit Current(Isc) | (A) | 8.95 | 9.01 | 9.06 | 9.12 | 9.17 |

*Under Nominal Module Operating Temperature (NMOT), Irradiance of 800W/ ㎡ , Spectrum AM 1.5, Ambient Temperature 20°C, Wind Speed 1m/s

TEMPERATURE CHARACTERISTICS

| | |
|---------------------------------|--------|
| Temperature coefficient of Pmax | -0.34% |
| Temperature coefficient of Voc | -0.27% |
| Temperature coefficient of Isc | 0.035% |
| NMOT | 44±2°C |

MECHANICAL DATA

| | |
|-------------------|----------------------------|
| Cell Type | Mono-Crystalline, 166*83mm |
| Cell Arrangement | 120pcs (2 (6×10)) |
| Dimension (L×W×H) | 1755 x 1038 x 35 mm |
| Weight | 19.2kg |
| Front Cover | 3.2mm Tempered Glass |
| Frame | Anodized Aluminium Alloy |
| Junction Box | IP67, 3 Bypass Diodes |
| Cable Type | 4mm² |
| Length of Cable | 1160mm |
| Connector | PV Connector |

OPTIONAL


| | |
|-------------|------------------|
| Frame | □ Black |
| Backsheet | □ Black |
| Connector | □ Original MC4 |
| Cable | □ 300mm □ 1160mm |
| Module Size | □ Customized |

PACKING MANNER

| | |
|-----------------|-------|
| Packing Type | 40'HQ |
| Piece/Pallet | 30 |
| Piece/Container | 780 |

*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, ECO DELTA POWER CO., LTD Reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the produccets described herein.

Current-Voltage Curve under different irradiance



Current-Voltage Curve under different working temperatures

