FIMER



C&I Storage system PVX-241

This new Energy Storage System is a modular solution with Hybrid Cooling and nominal capacity up to 241 kWh.
It is designed to offer an innovative and flexible solar solution for commercial and industrial applications.

241 kWh

Technical data

Model	PVX-241
System Data (PCS + Battery Packs)	
Nominal energy	241.0 kWh
Nominal capacity	314 Ah
Maximum cycle rate	0.45 CP
Rated voltage	768 V
Operative voltage range	648–852 V
Maximum current	221.2 A
Battery Parameters	
Battery pack model	ESM-60-2E1
Cell chemistry	LPF
Number of battery packs	4
Rated voltage	192 V
Reted current	140 A
Carching/Discharging Power	26.88 kW
Maximum charge/discharging current	183 A
Intra-battery rack balancing mode	Battery pack-level active balancing
PCS Parameters (AC)	
DCDC model	-
DCDC configuration of a battery rack	-
PCS model	PCS-108K-MB1
Three-phase three-wire or three-phase four-wire	Supported
Rated mains voltage	380 V/400 V/415 V
Rated charge and discharge current of the system	164.1 A @ 380 V_{AC} 155.9 A @ 400 V_{AC} 150.3 A @ 415 V_{AC}
Rated charge and discharge current of the system (1.1 times overload)	180.5 A @ 380 V_{AC} 171.5 A @ 400 V_{AC} 165.3 A @ 415 V_{AC}
Rated charge and discharge current of the system (1.2 times overload)	197.0 A @ 380 V_{AC} (1 min) 187.1 A @ 400 V_{AC} (1 min) 180.4 A @ 415 V_{AC} (1 min)
Rated charge and discharge current of the system (1.3 times overload)	213.4 A @ 380 V_{AC} (5s) 202.7 A @ 400 V_{AC} (5s) 195.4 A @ 415 V_{AC} (5s)
Maximum power	140.4 kW
Communication	
System communications port	Ethernet/Optical fiber (optional)/RS485
System communications protocol	Modbus TCP
Environmental	
IP rating	IP55
Operating temperature range	–30°C to +55°C (derated above 50°C)
Storage temperature range	–35°C to +60°C
Operating humidity range	0–100% RH (non-condensing)
Maximum operating altitude	4000 m
Noise limit (rated working conditions)	≤ 65 dB
General Specification	
Battery temperature control mode	Liquid cooling
LTMS model	TMS-H008SG00
LTMS quantity	1
Dimensions (W x D x H)	1150 mm x 1800 mm x 2100 mm
Weight	≤ 2.8 t
Surge protection	Type II (AC port)
Auxiliary mains power supply	176–300 V AC, single-phase, dual-live wire ≤ 5 kVA @ 0.45CP
Auxiliary power loss in standby mode (LTMS not started)	≤ 150.0 W
Thermal runaway suppression system	Aerosol (≥ 110 g)
Maximum efficiency	91,30%
Standards compliance	
Marking	RoHS 6
EMC	Class B
Safety Certifications	GB/T 36276, IEC 62619, IEC 62477-1; IEC 61000-3-12, etc.

FIMER

Remarks:
- **Features not specifically listed in the present data sheet are not included in the product**
- **Please refer to FIMER's Solar page for further details**

For more information please contact your local MA Solar Italy srl. representative or visit:

fimer.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. MA Solar Italy srl does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of MA Solar Italy srl. Copyright© 2025 MA Solar Italy srl. All rights reserved.