FIMER



Central Inverter 2MVA

PVS990-2000

Technical Specification

Product Type Designation	**PVS990-2000**
Input Parameters	
Max. DC voltage	1500 Vdc
DC Voltage operating range	935 - 1350 Vdc
Max. DC current	2300 A
Number of DC inputs	Up to 7nos
Output Parameters	
AC voltage	660 V ±10%**
Nominal AC Power	1700 kVA
Nominal AC current	1487 A
Maximum AC Power	2040 kVA
Maximum AC current	1785 A
Output Frequency	50 / 60 Hz
Power factor range (cos ϕ)	0...1 (Lead-Lag)
Harmonic Current Distortion (TDD)	≤3 %

©2026 FIMER India. All Rights Reserved.

Technical Specification

Product Type Designation	**PVS990-2000**

Efficiency

Maximum efficiency	≥ 99%
Euro efficiency	≥ 98.8%

Protections

DC Protection	Fuses & Motorized Load break switch
AC Protection	Air Circuit Breaker
Surge Protection	AC & DC Type 1+2
Anti-islanding	Yes
Insulation and Ground fault monitoring	Yes
Over temperature protection	Yes
Emergency Power Off switch	Yes

Features

Paralleling	Yes
Grid support	Yes
MPPT	Single
Night VAR compensation	Yes
Multi master communication	Up to 5 masters

General Data

Degree of Protection	IP65 Outdoor
Dimension (WxHxD)	956x 2300x 2000 mm
Total Weight	1500 kg (approx.)
Operating Temperature	-20°C ...+60°C (Derating starts from 52°C)
Cooling Method	Forced Air Cooling
Operating Altitude	Upto 4000m
Relative Humidity (Non Condensing)	5 ... 95 %
Corrosion class	C4, (C5 optional)

Certifications and Approvals*

IEC, UL, EN, BDEW, CEI and more.

*Under Certification
** 600V, 630V, 690V AC voltage rating models are available upon request.

For more information please contact your local FIMER representative or visit: **fimer.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER. Copyright© 2026 FIMER. All rights reserved.

FIMER_PVS990-2000_F1-2605-362_Rev00_27.05.2026