

Mouth Simulator according to ITU-T Rec. P51



Y.

ITU-T rec.: P.51 IEEE standards: 269, 661 GRAS 44AB Mouth Simulator is a sound source which simulates the sound field around the human mouth at close quarters and complies with the Standards IEEE 269, 661 and ITU-T Rec. P51.

GRAS 44AB is for testing telephone mouthpieces as well as other microphones similarly used in communication networks.





At the mouth reference point (MRP), which is 25mm from the detachable lip ring (35mm from the mouth of the Type 44AB), the maximum continuous signal

it can produce in  $1/_3$ -octave bands is 100dB re. 20µPa in the frequency range 100Hz to 16kHz. Its loudspeaker accepts an external signal directly via a BNC input.

Jigs are included for calibration according to CCITT P.51 and IEEE 269. These are for use with  $\frac{1}{4}$ " or  $\frac{1}{2}$ " microphones. One jig holds the microphone at 0° incidence ( $\frac{1}{4}$ " only) to the sound source, the other at 90° incidence ( $\frac{1}{4}$ " or  $\frac{1}{2}$ ").

NOTE: This type of mouth simulator can not be mounted inside a KEMAR head.




Connector type		BNC
ITU-T recommondations		P.51
IEEE standard		269, 661
Maximum power, continuous	W	10
Maximum power, pulsed 2 sec.	W	50
Temperature range, operation	°C / °F	10 to 35 / 50 to 95
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Weight	g / oz	1000 / 35.274

Maximum continuous output level at MRP [200 Hz - 6 kHz] 110 dB re. 20 Pa

Maximum continuous output level at MRP [100 Hz - 16 kHz] 100 dB re. 20 Pa

Distortion 250 Hz - 8 kHz (Linear signal @ 94 dB at MRP) typically 1 %, max. 1.5 %



## Frequency response

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Page: 3



Included		
GRAS RA0104	Jig (CCITT P51)	
GRAS RA0105	Jig (IEEE 269)	
Optional		
GRAS RA0110	Conical mouthpiece	

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

. . . . . . . . . . . . . .

# **GRAS Worldwide**

Subsidiaries and distributors in more than 40 countries

#### HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.gras.dk gras@gras.dk

#### JSA

GRAS SOUND & VIBRATION 5750 S.W. Arctic Drive Beaverton, OR 97005 Tel: 503-627-0832 Toll Free: 800-231-7350 www.gras.us sales@gras.us

#### CHINA

**GRAS SOUND & VIBRATION** Room 303, Building T6 Hongqiaohui, 990, Shenchang Road Minhang District, Shanghai China. 201106 Tel: +86 21 64203370 www.gras.com.cn cnsales@gras.dk

### **ABOUT GRAS SOUND & VIBRATION**

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

