

# GA-12

*plus*

madur

portable gas analyser

www.madur.com



## CHARACTERISTIC

FEATURES

TECHNICAL DATA

SENSORS

EQUIPMENT

APPEARANCE

A further development from the tried and tested GA-12 hand-held analyser.

GA-12plus can be equipped with up to 4 electrochemical cells. By default fitted with Li-ion battery.

Suitable for a soot test using electronically controlled gas volume.

It holds big memory capable of storing 32 measurement reports.

Manufactured according to the principles of EN50379.

An attractive alternative to other, bigger analysers.

# GA-12 *plus*

CHARACTERISTIC

FEATURES

TECHNICAL DATA

SENSORS

EQUIPMENT

APPEARANCE

- Equipped with 3 or 4 electrochemical cells (typical configuration: O<sub>2</sub>, CO, NO/NO<sub>x</sub>, SO<sub>2</sub>)
- Works with an external portable printer via wireless communication (IR LED)
- Built-in rechargeable Li-ion battery for up to 16 hours of operation
- Probe holder with a standard M30x1 fitting, fits all madur gas probes with the K-type or S-type thermocouples
- Availability of soot measurements (with proper probe holder)
- Built-in pressure sensor for chimney draft measurements and continuous pump flow control
- Optional differential pressure sensor - for measurements of chimney draft and flow velocity (with help of Pitot tube)

NOTE that two versions of analyser are available:

standard version with single pressure sensor

version with additional differential pressure sensor (that allows to perform measurements of gas flow velocity)

- Cooperation with digital RH and temperature probe
- Measurements of gas and ambient temperatures
- Results presented on LCD display (128 \* 64) with back-lighting
- Built-in large memory for results
- Firmware for gas calibrations
- Calculations of many additional parameters



# GA-12 *plus*

## CHARACTERISTIC | FEATURES | TECHNICAL DATA | SENSORS | EQUIPMENT | APPEARANCE

GA-12plus GAS ANALYSER	VERSION A	VERSION B		
	SINGLE PRESSURE SENSOR	SECOND DIFFERENTIAL PRESSURE SENSOR		
Dimensions (W * H * D)	243 mm * 130 mm * 60 mm			
Dimensions with gas connectors (W * H * D)	257 mm * 130 mm * 60 mm	271 mm * 130 mm * 60 mm		
Weight (4-sensors) without accessories	615 g	635 g		
Casing material	ABS case, rubber protective boot (optional)			
Operating conditions	T: 10°C ÷ 50°C RH: 5% ÷ 90% (non-condensing)			
Storing temperature	-20°C ÷ +55°C			
Power supply	Built-in Li-ion rechargeable battery (1600 mAh)			
Operating time (fully charged battery)	Up to 16h			
Number of gas sensors	3 or 4			
Data memory	64 measurement reports			
Display	Graphical LCD 128 * 64 with variable contrast and LED backlighting			
Printer	External thermal IR printer MCP 8850 with charger			
Gas pump	Diaphragm, max 0,6 ÷ 0,9 l/min			
Communication interface with PC computer	RS-232C			
Gas filtering	In-line filter included in the gas probe hose			
<b>MEASUREMENTS</b>				
Variable	Method	Range   Resolution	Accuracy	Time (T <sub>90</sub> )
T <sub>gas</sub> - gas temperature	K-type thermocouple	-10 ÷ 1000°C   0,1°C	± 2°C	10 sec
T <sub>gas</sub> - gas temperature	S-type thermocouple	-10 ÷ 1000°C   0,1°C	± 2°C	10 sec
T <sub>amb</sub> - boiler intake air temperature	PT500 resistive sensor	-10 ÷ 100°C   0,1°C	± 2°C	10 sec
Differential pressure	Silicon piezoresistive pressure sensor	-25 hPa ÷ +25 hPa   1 Pa (0,01hPa)	± 2Pa abs. or 5% rel.	10 sec
Gas flow velocity (optional)	Indirect, with Pitot tube & second pressure sensor	1 ÷ 50 m/s   0,1 m/s	0,3 m/s abs. or 5% rel.	10 sec
Lambda λ- excess air number	Calculated	1 ÷ 10   0,01	± 5% rel.	10 sec
qA - stack loss	Calculated	0 ÷ 100%   0,1%	± 5% rel.	10 sec
Eta η - combustion efficiency	Calculated	0 ÷ 120%   0,1%	± 5% rel.	10 sec
RH- relative humidity (special probe needed)	SHT11 capacitive polymer sensor	5 ÷ 95%   1%	± 5% abs.	30 sec

# GA-12 *plus*



CHARACTERISTIC | FEATURES | TECHNICAL DATA | **SENSORS** | EQUIPMENT | APPEARANCE

Method	Range   Resolution	Accuracy	Time (T <sub>90</sub> )	Conformity
<b>O<sub>2</sub> - OXYGEN</b>				
Electrochemical	20,95%   0,01%	± 0,01% abs. or 5% rel.	45 sec	EN 50379; CTM-030
Electrochemical	25,00%   0,01%	± 0,01% abs. or 5% rel.	45 sec	EN 50379; CTM-030
<b>CO - CARBON MONOXIDE</b>				
Electrochemical	2 000 ppm   0,1 ppm	± 5 ppm abs. or 5% rel.	45 sec	EN 50379; CTM-030
Electrochemical	4 000 ppm   1 ppm	± 5 ppm abs. or 5% rel.	45 sec	EN 50379; CTM-030
Electrochemical	20 000 ppm   1 ppm	± 10 ppm abs. or 5% rel.	45 sec	EN 50379; CTM-030
Electrochemical	10%   0,001 %	± 0,005% abs. or 5% rel.	45 sec	EN 50379; CTM-030
Electrochem., with H <sub>2</sub> compensation	4 000 ppm   1 ppm	± 5 ppm abs. or 5% rel.	45 sec	EN 50379; CTM-030
<b>NO - NITRIC OXIDE</b>				
Electrochemical	2 000 ppm   0,1 ppm	± 5 ppm abs. or 5% rel.	70 sec	EN 50379; CTM-030
<b>NO<sub>2</sub> - NITROGEN DIOXIDE</b>				
Electrochemical	1 000 ppm   0,1 ppm	± 5 ppm abs. or 5% rel.	45 sec	EN 50379; CTM-030
<b>SO<sub>2</sub> - SULPHUR DIOXIDE</b>				
Electrochemical	2 000 ppm   0,1 ppm	± 5 ppm abs. or 5% rel.	45 sec	EN 50379
<b>H<sub>2</sub>S- HYDROGEN SULPHIDE</b>				
Electrochemical	2 000 ppm   0,1 ppm	± 5 ppm abs. or 5% rel.	45 sec	

## STANDARD EQUIPMENT

### SUPPLIED ALONG WITH THE DEVICE

- Carrying case for analyser and accessories
- Power supply (charger) for the built-in Li-ion battery with selected type of mains plug
- Comparison scale with paper filters for the soot test
- Software CD with program and manuals
- 2,5m RS-232C communication cable with DB9 female connector

## ADDITIONAL EQUIPMENT

### NECESSARY FOR THE ANALYSER TO WORK

- Probe holder

Together with an exchangeable gas probe pipe the holder is a complete gas probe for extraction of gas samples. It has a single gas tube ended with quick coupler and electric cable ended with a 4-pin connector. Gas probe pipe is mounted with a M30x1 fastening.

Probe holder is equipped with an in-line filter with a condensation trap (pore size of the filter inlet is 5µm). Probe holder is available in two versions:

- heated (with a slit for a filter for soot measurement test),
- unheated (without a possibility to perform soot test).



- Gas probe pipe

Gas probe is immersed in the gas duct and is supposed to extract the gas sample and to measure its temperature.

Exchangeable probes are easily connected to probe holders (with M30x1 fastening). They have thermocouple type K (in some configurations type S) for measurement of gas temperature and a threaded fixing cone. With the probe holder is a complete gas probe.

There are many probe pipes available. They differ in length and working temperature.

For work efficiency it is advised to own different probe pipes to be able to adjust to the measurement place.



## OPTIONAL EQUIPMENT & SPARE PARTS

- Portable printer & printer paper

Portable printer (battery operated), communicates with the analyser via wireless HP-IR interface. Allows to print measurement results instantly on the 58mm thermal paper.

The printer is delivered together with 4 Ni-MH rechargeable batteries and a single roll of paper. The mains adapter for the charger can be ordered appropriately in the AU/EU/UK/US version.

ordering codes:

printer - M20-2DHP2

battery charger with EU plug - M20-2DHP1

battery charger with US plug - M20-2DHP3

battery charger with UK plug - M20-2DHP4

58mm thermal paper roll - V-THP5701



- RH and ambient temperature probe

Probe for RH and ambient temperature measurements.

Not-suitable for inside stack measurements (working temperature up to 120°C).

ordering code:

Z14-SON-HUM



- Ambient temperature sensor

This ambient temperature sensor on a 3m cable is used for measurement of the boiler's inlet air.

ordering code:

Z12-SENS-TEMP



# GA-12 *plus*

CHARACTERISTIC | FEATURES | TECHNICAL DATA | SENSORS | **EQUIPMENT** | APPEARANCE

- Anchor cone for PT-500 ambient temperature sensor

This cone allows fitting the temperature sensor into holes with different diameter.

ordering code:  
Z14-CONE-PT500



- Magnetic holder for PT500 sensor

This magnetic holder allows to safely hang the sensor on a metal surface.

ordering code:  
Z14-MAGN-PT500



- Pitot tube

Pitot tube is an accessory that allows to perform measurement of the flow velocity of the gas stream. The measurement is performed indirectly – Pitot tube is connected to analyser’s differential pressure sensor. Analyser recalculates the differential pressure on the Pitot tube’s outlets to velocity.

A few lengths of tubes are available. Pitot tube has 2m gas tubings to connect it with the analyser.

ordering codes:  
pitot tube 800mm - Z00-PITOT-8002  
pitot tube 500mm - Z00-PITOT-5002



- RS232C to USB converter

2.5m cable that allows to connect the analyser (its RS232C port) with USB port in PC computer (especially valuable when PC is not equipped with COM port).

ordering code:  
Z12-USB-ADAP



- Bluetooth communication module

Module connected to the analyser’s RS232C port, allows to communicate with PC computer over Bluetooth protocol.

ordering code:  
Z12-BLUE-TOOTH



- Leatherette casing

Soft casing (for the analyser alone) made from leatherette, protects the analyser during transport.

ordering code:  
Z14-ETUI1



- Rubber protector

Special rubber protector for the analyser’s casing. Protects the analyser against hits and blows. Shoulder strap eases carrying the analyser.

ordering code:  
Z14-RUBBER-001



- Pressure kit

Pressure kit allows to perform leakage test of the pneumatic / gas installations. Requires differential pressure sensor to operate.


ordering code:  
Z02-LEAK-TEST-KIT



- Li-ion rechargeable battery

Rechargeable Li-ion battery, 3,6V, 1600mAh (or better).

ordering code:  
Z14-BAT-CHARGER\_02



- In-line filter

In-line filter for all the types of GA-12 probes and GA-12<sup>plus</sup> probe holders.

ordering code:  
Z14-FILTER-INLINE



- In-line filter insert 12mm/5µm and 12mm/20µm

Filter insert for all the types of in-line filters.

ordering codes:  
5µm insert - V-FELM082  
20µm insert - V-FELM252



# GA-12 *plus*

CHARACTERISTIC

FEATURES

TECHNICAL DATA

SENSORS

EQUIPMENT

APPEARANCE

## FRONT PANEL

VERSION WITH A SINGLE PRESSURE SENSOR



VERSION WITH AN ADDITIONAL

DIFFERENTIAL PRESSURE SENSOR



## ANALYSER'S CARRYING CASE

## PU FOAM INSERT TO THE CASE



# GA-12 *plus*

CHARACTERISTIC | FEATURES | TECHNICAL DATA | SENSORS | EQUIPMENT | APPEARANCE

## EXAMPLE PRINTSCREEN

```

1 Action
HOLD - *
Pressure test
Soot test
Ambient CO test
Leakage test
Esc  OK  ++
    
```

```

1 1/3 Triple
19.53 | 20.48 | %O2
0.89  | 0.30  | %CO2
1      | 0       | ppmCO
---   | ---    | ppmNOx
Esc   | 1-2-3 | ++
    
```

```

2 Action
▶ Set pressure to zero
Calibrate O2 for 20.95%
Esc  OK  ++
    
```

```

21.00
19.96
%
O2
-34.5
19.60
Esc  Options
    
```

## EXAMPLE SCREENSHOT FROM THE PC PROGRAM

**Analyzer printouts defining**

User defined strings

0	
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	

Operator: \_\_\_\_\_

**Printout preview**

PrintOut 1 | PrintOut 2 | PrintOut 3 | PrintOut 4

```

1 -----#1-----
      m a d u r
      GA-12plus #00000000
      =====
1 Report:      1-2-3 #0000
      01-01-01      12:57
      Light oil      1
      Averaging time: 2 min
5 Client nr:      00001
      Operator:
      =====
      O2              5.12 %
      CO2             10.04 %
10 CO               163.2 ppm
      NO              163.2 ppm
      NOx             78.8 ppm
      TOX ---
      =====
15 CO in mg        204 mg/Nm3
      ...
    
```

Line: 1 Code: 42

**Results**

[Dropdown]

**Special lines**

Report: 1-2-3 #0000

**User defined strings**

[Dropdown]

**Separating lines**

[Dropdown]

No line

Empty line

Remove line

Insert line

Print partial results

Fast printer

Send to analyzer

Open file...

Save

Default

Close