

# Guidelines Pop-Up



- Filer skal leveres printklar i færdigt format med 5 mm bleed til beskæring top, bund og sider.
- Printfiler leveres med trim og bleed mærker.
- Tekster/fonte konverteret til kurver/outlined/vektoriseret.
- Alle farver - herunder også billedfiler - skal være defineret i CMYK.
- Ved specialfarver vedlægges farveprøve eller pantone nummer (Vi kan kun tilnærmelsesvis ramme pantonefarver).
- Filer laves som samlet grafikflade - ikke baneopdelt.
- Filer skal ligge som enkeltsidet grafik (ikke 2 eller flere sider i samme fil).
- Anbefalet opløsning er 125 dpi i 1:1 og skal minimum være 80 dpi.

Evt. DtP arbejde afregens efter gældende timesats.



- Files must be delivered ready-to-print in finished format with 5 mm bleed at top, bottom and sides for cropping
- Print files delivered with trim and bleed marks.
- Texts/fonts converted to curves/outlined/vectorised.
- All colours - also images - must be defined as CMYK.
- If special colours has been used, a colour sample must be forwarded or pantone number must be added (we can only a just to colours defined in pantone number).
- Files created as 1 total graphic surface - not divided into panels.
- Files must be generated as single pages (not 2 or more pages in the same file).
- Recommended resolution is 125 dpi in scale 1:1 and minimum must be 80 dpi.

Additional desktop work will be invoiced according to the current hourly rate.

