



Guidelines for opsætning af filer til print

- Filer skal leveres printklar i færdigt format.
- Printfiler leveres uden trim og bleed mærker.
- Tekster/fonte konverteret til kurver/outlined/vektoreret.
- Alle farver - herunder også billedfiler - skal være defineret i CMYK.
- Ved specialfarver vedlægges farveprøve eller pantone nummer (Vi kan kun tilnærmelsesvis ramme pantonefarver).
- Filer skal ligge som enkeltsidet grafik (ikke 2 eller flere sider i samme fil).
- Anbefalet opløsning er 125 dpi i 1:1 og minimum skal være 80 dpi.

Evt. DTP arbejde afregens efter gældende timesats.



Guidelines for preparing files for printing

- Files delivered as print ready files at correct size.
- Print files delivered without trim and bleed marks.
- Texts/fonts converted to curves/outlined/vectorised.
- All colours - also images - must be defined as CMYK.
- If special colours have been used, a colour sample must be forwarded or pantone number must be added (we can only do just to colours defined in pantone number).
- Files must be generated as single pages (not 2 or more pages in the same file).
- Recommended resolution is 125 dpi in scale 1:1 and minimum must be 80 dpi.

Additional desktop work will be invoiced according to the current hourly rate.