



Integrated Gas Technologies

GAS ALARM

Combustible gas detector GA850 series



GA850-001 / GA850-003



GA850-002

MAIN FEATURES

- Human voice prompt
- High reliable catalytic combustion method
- Gas concentration displaying (PPM)
- Power supply from AC 90V-240V or 9V rechargeable battery
- Intelligent microprocessor control
- Auto low battery warning
- Low battery warning
- Alarm memory function
- Auto detect sensor failure

TECHNICAL SPECIFICATION

Model No.	GA850-001	GA850-002	GA850-003
Detecting gas type	LPG and natural gas		1. Carbon monoxide & 2. LPG & natural gas
Led display	Yes	N/A	Yes
Alarm Density	2500PPM(±1500PPM)		1. 100PPM-999PPM(±50PPM) 2. 6%-20% LEL(3,000PPM-10,000PPM±1,500PPM)
Alarm time	keep alarming after over 2500PPM		vocal alert & siren alarm
Material	ABS Plastic		
AV voltage	AC 90V-240V		
Battery voltage	9V rechargeable battery(optional)		
Warm-up Time	About 180S		
Working temperature	0°C-50°C		
Environment Humidity	10%-95%		
Sound Level	85dB/m		
Size	112×73×42MM		

APPLICATION PLACE



Hospital



Apartment



Hotel



Supermarket



Villa



Bank



Office



Government



INTEGRATED GAS TECHNOLOGIES ApS

Gydevang 39-41, 3450 Allerød Denmark.

E-Mail: sales@igt-lpg.com - Tel: +45 45 76 99 21



Scan Qr Code to Visit Our Website
www.igt-lpg.com