




Constant Voltage Driver

Model: XSV Series



Model	Rated Input Voltage	Input Power	Input Current	PF	Output Power Range	Output Voltage	Output Current	Efficiency (typ.)
XSV60W48	220-240VAC	≤72W	≤0.4A	≥0.95	0-60W	48V	1.25A	88%
XSV100W48		≤115W	≤0.6A		0-100W		2.1A	90%
XSV160W48		≤180W	≤0.9A		0-160W		3.34A	92%
XSV240W48		≤265W	≤1.5A		0-240W		5A	92%
XSV400W48		≤435W	≤2.3A		0-400W		8.34A	93%

* Test result @230V, 50Hz, Full Load.

1. Parameters

category	Item	Technical Norm			
Features	Output Type	Constant Voltage			
	Dimming Type	NA			
	Output Features	Isolation SELV			
	IP Grade	IP67			
	Installation	Independent			
	Insulation Class	Class I			
Input	Rated Input Voltage	220-240VAC			
	Range of AC Input Voltage	176-264VAC			
	Range of DC Input Voltage	175-280VDC (EMI not evaluated)			
	Frequency	Rate:50/60Hz, Range:47~63Hz			
	Power Factor	≥0.95, 220-240VAC, Rated Load, see graphs			
	THD	≤10%, 230VAC, Rated Load, see graphs			
	No Load Power Consumption	≤0.5W, @230VAC			
	Inrush Current	Model	IP (typ.)		
60W		<30A	26A	220us	240Vac/50Hz, 90-degree phase, full load, cold start-up, duration time measure from 50%Ipk to
100W		<50A	45A	250us	
160W		<60A	56A	250us	

		240W	<80A	76A	320us	50%Ipk	
		400W	<100A	88A	430us		
	Connected quantity of 16A Breaker	60W	16pcs,16A type B / 26pcs 16A type C				
		100W	10pcs,16A type B / 16pcs 16A type C				
		160W	8pcs,16A type B / 13pcs 16A type C				
		240W	6pcs,16A type B / 8pcs 16A type C				
	400W	4pcs,16A type B / 5pcs 16A type C					
Output	Output Voltage	48VDC±3%					
	Rated Load Range	60W	24-60W				
		100W	30-100W				
		160W	48-160W				
		240W	72-240W				
		400W	120-400W				
	Output Voltage Ripple	<480mV _{PK-PK} (0.5%)					
	Line Regulation	±1%					
	Load Regulation	±2%					
	Overshoot	<105%V _o					
	Start-up Time	<0.5S (220-240VAC)					
	Efficiency	60W	≥86%	88% typ.	230VAC, Rated Load, at output terminals, see graphs		
		100W	≥90%	92% typ.			
160W		≥90%	92% typ.				
240W		≥90%	92% typ.				
400W		≥91%	93% typ.				
Protection	Short Circuit Protection	Auto Recovery					
	Over Current Protection	120%-200%I _o , Auto Recovery					
	Over Voltage Protection	120%-150%V _o , Auto Recovery					
	Over Temperature Protection	90<T _c <110°C, Auto Recovery					
	Insulation voltage	I/P to O/P,3KV _{ac} /5mA/1min					
	Insulation resistance	>100M ohm @ 500VDC					
	Leakage current	I/P to O/P < 250μA					
Environment	Ta/Operation Temperature	-25....+50°C					
	Ts/Storage Temperature	-40....+85°C					
	Tc/Enclosure Temperature For Safety	60W/100W	75°C				
		160W	85°C				
		240W/400W	90°C				
	Humidity	5%....85%RH					
Atmosphere	86-108KPa						
Standards	Certification	CE					
	Safety Standards	EN61347-1:2015, EN61347-2-13:2014/A1:2017, EN62493:2015, AS61347.2.13:2018, AS/NZS 61347.1:2016 Inc A1					
	EMC Standards	EN55015:2013/A1:2015, EN61000-3-2:2014, EN61000-3-3:2013, EN61547:2009					


	Performance	EN62384		
	Surge	L-N:4KV, L/N-PE:6KV		
Others	RoHS	2011/65/EU		
	MTBF	≥250KHours, Ta=25°C (MIL-HDBK-217F)		
	Audible Noise	<25dB @ 10cm distance, 20dB background		
	Life Time	30W/60W/100W/160W	≥100K Hrs 65 °C case temperature, refer to life vs. Tc curve	
		240W/400W	≥100K Hrs 75 °C case temperature, refer to life vs. Tc curve	
	Warranty	5years		
	Dimensions (L*W*H)	60W	275*30*21MM (body), 290*30*21MM (endcaps included)	
		100W	305*30*21MM (body), 320*30*21MM (endcaps included)	
		160W	335*30*21MM (body), 350*30*21MM (endcaps included)	
		240W	385*30*21MM (body), 400*30*21MM (endcaps included)	
400W		380*60*22MM (body), 400*60*22MM (endcaps included)		
Wiring	Input	H05RN-F/3X1.0mm ² , Brown/Blue/(Yellow/Green)		
	Output	H05RN-F/2X1.0mm ² , Brown/Blue		
Output Cable Length	Max. 3M			

Remark:


1. All Parameters, if not specified, are measured at 230VAC/50Hz and 25°C ambient temperature.
2. LED Driver is a component of the luminaires, Luminaires and wire layout will affect the EMC, please check the EMC with end products again.
3. Output ripple should be measured at the output end which has with 0.1uF/100V ceramic capacitance and 10uF/100V Aluminum capacitance connected in parallel. Measured using oscilloscope with bandwidth limited to 20MHz.

2. Graph


PF VS LOAD Curve




THD VS LOAD Curve



Efficiency VS LOAD Curve



Lifetime vs. Case Temperature



(End of Life: Maximum Failure Rate=10%)

3. Label

<ul style="list-style-type: none"> ○ L (Brown) ○ N (Blue) Ⓢ (Yellow-green) 	<p>KGP KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid</p>	<p>XSV60W48 LED Driver Constant Voltage Type For LED modules only</p>	<p>Input: 220-240V~, 50/60Hz, 0.4A, λ:0.95 Output: 48V- 0-1.25A Max.60W *tc Ta: -25 ~ +50°C Tc:75°C</p> <p>SELV CE ENEC IP67</p>	<p>(Blue) + (Brown) + output</p>
---	--	---	---	----------------------------------


<ul style="list-style-type: none"> ○ L (Brown) ○ N (Blue) Ⓢ (Yellow-green) 	<p>KGP KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid</p>	<p>XSV100W48 LED Driver Constant Voltage Type For LED modules only</p>	<p>Input: 220-240V~, 50/60Hz, 0.6A, λ:0.95 Output: 48V- 0-2.1A Max.100W *tc Ta: -25 ~ +50°C Tc:75°C</p> <p>SELV CE ENEC IP67</p>	<p>(Blue) + (Brown) + output</p>
---	--	--	---	----------------------------------

<ul style="list-style-type: none"> ○ L (Brown) ○ N (Blue) Ⓢ (Yellow-green) 	<p>KGP KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid</p>	<p>XSV160W48 LED Driver Constant Voltage Type For LED modules only</p>	<p>Input: 220-240V~, 50/60Hz, 0.6A, λ:0.95 Output: 48V- 0-3.34A Max.160W *tc Ta: -25 ~ +50°C Tc:85°C</p> <p>SELV CE ENEC IP67</p>	<p>(Blue) + (Brown) + output</p>
---	--	--	--	----------------------------------


<ul style="list-style-type: none"> ○ L (Brown) ○ N (Blue) Ⓢ (Yellow-green) 	<p>KGP KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid</p>	<p>XSV240W48 LED Driver Constant Voltage Type For LED modules only</p>	<p>Input: 220-240V~, 50/60Hz, 1.5A, λ:0.95 Output: 48V- 0-5A Max.240W *tc Ta: -25 ~ +50°C Tc:90°C</p> <p>SELV CE ENEC IP67</p>	<p>(Blue) + (Brown) + output</p>
---	--	--	---	----------------------------------

<ul style="list-style-type: none"> ○ L (Brown) ○ N (Blue) Ⓢ (Yellow-green) 	<p>KGP KGP Electronics GmbH Hueckstraße 19 DE-58511 Lüdenscheid</p>	<p>XSV400W48 LED Driver Constant Voltage Type For LED modules only</p>	<p>Input: 220-240V~, 50/60Hz, 2.3A, λ:0.95 Output: 48V- 0-8.34A Max.400W *tc Ta: -25 ~ +50°C Tc:90°C</p> <p>SELV CE ENEC IP67</p>	<p>(Blue) + (Brown) + output</p>
---	--	--	--	----------------------------------


4. Dimension (Unit: mm) XSV60W48




XSV100W48




XSV160W48




XSV240W48



XSV400W48



5. Wiring Diagram



6. Packing information

Model	Carton L*W*H(cm)	Pcs/ Carton	Net weight/ Pcs(g)	Net weight/ Carton(kg)	Gross weight/ Carton(kg)
XSV60W48	34*29*20	28	390	11.3	12.8
XSV100W48	39*29*20	28	420	12.0	13.7
XSV160W48	39*29*20	28	470	13.5	15.2
XSV240W48	44*29*14	24	530	10.2	11.5
XSV400W48	44*29*14	12	1050	12.2	13.2

7. REVISION HISTORY

Date	Revision	Remark
2021-12-06	A	Preliminary Edition
2022-3-06	B	Standard Edition
2024-5-17	C	Add ENEC certification mark
2024-08-12	D	Add life vs. Tc curve