

# DM700K-N

## Manual Call Point Red, 2-Position Keyswitch, Surface Mount

### General

---

The DM700K-N is a high quality, red plastic manual call point with key switch. It allows for on/off control of equipment such as ventilation and overrides.

The key switch has 2 positions, with the key being trapped in one position and removable in the other. Changing between these positions require the turn of the key through a 90° angle. It offers three electrical connections, which already come fitted with flying leads. One of these connections are common, while the turning of the key result in the change over between the other two.

### Construction

---

The robust switching device comprises a main housing and escutcheon plate. It is fitted to the plate which simply snaps into the main housing and is permanently located in place with fixing screws. All units are supplied with 2 sturdy keys.



### Details

---

- Easy to install
- High quality key switch
- Operates after long period of disuse
- Preformed mounting slots
- EN54 'burning house' functional marking
- Surface mount

# DM700K-N

## Manual Call Point Red, 2-Position Keyswitch, Surface Mount

### Technical specifications

#### Physical

Physical dimensions	87 x 87 x 52 mm (W x H x D)
Net weight	166 g
Colour	Red

#### Environmental

Operating temperature	-20 to +55°C
Relative humidity	0 to 90% noncondensing
Environment	Indoor
IP rating	IP21

#### Electrical (switch specifications)

Maximum voltage	250 Vac
Maximum current	2A @ 250 Vac
	4A @ 125 Vac
	4A @ 28 Vdc

#### Mechanical

Functional marking	EN54 burning house
--------------------	--------------------