


ACTIVE SPLITTER

IS YOUR ICS LOW ON HEADSET CONNECTIONS -OR HAVING AN ISSUE WITH INCOMPATIBLE HEADSET TYPES? IWCS ACTIVE SPLITTER SAVES YOU ANOTHER COMMUNICATION ACCESS PANEL



FEATURES

The ACTIVE SPLITTER from IWCS addresses several commonly occurring requirements for aviation crews. It provides easy connection of two headsets while occupying only one port on your ICS, potentially doubling the headset capacity of your ICS. The ACTIVE SPLITTER creates full intercom between the attached headsets and offers independent volume control for each. The ACTIVE SPLITTER can also function as impedance matching and provide signal amplification for those situations where you run into incompatibility between headset and ICS. Each headset port on the ACTIVE SPLITTER is independently configured for the specific headset type.


CONFIGURATION OPTIONS

ICS-type: Dynamic or Amplified Microphone Input Headset 1 input: Dynamic or Amplified Mic. Input Headset 2 input: Dynamic or Amplified Mic. Input Independently selectable microphone gain for each headset connection

Independently selectable (ON/OFF) 24V phantom supply for each headset connection

Independently selectable phantom supply impedance for each headset connection

Independently selectable connector wiring for each connection (NATO-US/Savox/Peltor)



TECHNICAL SPECIFICATIONS

Connections: TP-108 (ICS) / 2x TJ-108 (Headsets) Wiring: NATO-US/Savox/Peltor Supply voltage: 24-32VDC (28VDC Nom) Configurable 0-60dB

Voltage feed-through for headset ANR Passive dynamic or amplified microphone types 24V Phantom supply for amplified microphone Independent volume control

Mic. amp.:

IR-46-TX108-01-XXX Part number:

