



# JETAIR 100270

## JETTING FTTX BLOWING COMPRESSOR

The compact engine-driven (gasoline) compressor makes FTTX installations easier and more flexible in the field. With a free air delivery of approximately 3.5 CFM at 116 psi, and with an integrated aftercooler and humidity filter, this compressor supports your fiber blowing work perfectly and allows you to operate completely independent of external power supply.

JetAir 100270 is designed for fiber blowing in micro-ducts with internal diameters up to 0.16 in. Its lightweight yet robust construction makes transport and setup quick and easy. Combined with Jetting's Trigg AIR or the V0 fiber blowing machine, it provides a reliable and efficient solution for smaller installation projects.



## JETAIR 100270

- Max pressure: 145 psi
- Free Air Delivery (FAD): approx. 3.5 CFM @ 116 psi
- Intake air flow: approx. 9.5 CFM
- Engine: Subaru Robin, 3 HP (manual start)
- Built-in aftercooler and water separator
- Oil-free air delivery
- Outlet: 1 x 3/8" CEJN connector
- 4-stroke engine
- Vibration-dampening rubber feet
- Suitable for micro-duct jetting up to: Ø 0.16 in
- Fuel type: 95 octane (≈ 91 AKI US unleaded)
- Fuel tank: 0.9 US gal
- Noise level: 80 dB(A) LpA / 94 dB(A) LwA
- Dimensions (L x H x W): 20.1 x 16.5 x 12.0 in
- Weight: 54.0 lb
- Article number: 660506

