




Air Boy® Classic

Robust and impact resistant, infinitely adjustable, leak free

Blowgun with 300mm straight pipe, ø8mm

The JWL ergonomic design is a classic in itself. We use the compressed air to ease the activation of the handle making it easy, precise and simple to operate.

The Air Boy® Classic is produced in an impact-resistant acetal plastic (POM)





The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Materials		Specifications			Directives		
Handle and trigger	Acetal plastic	P	Max 16 bar		2003/10/CE	Max 85 dB	OK
Valve	Acetal plastic		380 l/min (8 bar)		OSHA 1910.95 (b)	Max 90 dB 8 hr	ОК
Gaskets / O-rings	Nitrile		85 dB (8 bar), 84 dB (6	5 bar)	OSHA STD 1-13.1	Max 30 psi when blocked	-
Blowing tube & shaft	Steel, el. galvanised	-10°C to +80°C					
Spring	Hardened spring wire		~0,138 kg				
Flow	l/min(cfm) / bar(psi)	Noise level dB / bar(psi)			Blowing force	Newton (g) / ba	ır(psi)
600 (21,19) 500 (17,66) 400 (4,13) 300		100 90 Measured at a distance of 1m to the side of the nozzle 80 80 80			6 (612) Measured on a 400 x 400mm plate at a distance of 150 mm from the nozzle (408) 3,92		

60 50



200

100