


DIN 444B 4.6 KNEVELSCHROEVEN – ELEKTROLYTISCH VERZINKT

DIN 444B 4.6 EYE BOLTS – STEEL ZINC PLATED

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER ELECTOR-ZINGUE

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL VERZINKT



ISO :-
DIN : 444B
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P		0,8	1	1,25	1,5	1,75	2
	1	16	18	22	26	30	34
b	2	-	-	28	32	36	40
	3	-	-	-	-	49	53
d2 (H9)		5	6	8	10	12	14
d3 (max.)		12	14	18	20	25	28
S (max.)		6	7	9	12	14	16
d		M5	M6	M8	M10	M12	M14
LENGTE							
25		26180050025	26180060025	26181080025	26180100025	26181120025	
30		26181050030	26181060030	26181080030	26181100030	26181120030	
35		26181050035	26181060035	26181080035	26181100035	26181120035	
40		26181050040	26181060040	26181080040	26181100040	26181120040	
45			26181060045	26181080045	26181100045	26181120045	
50			26181060050	26181080050	26181100050	26181120050	26181140050
55			26181060055	26181080055	26181100055	26181120055	26181140055
60			26181060060	26181080060	26181100060	26181120060	26181140060
65			26181060065	26181080065	26181100065	26181120065	26181140065
70			26181060070	26181080070	26181100070	26181120070	26181140070
75			26181060075	26181080075	26181100075	26181120075	26181140075
80			26181060080	26181080080	26181100080	26181120080	26181140080
85				26181080085	26181100085	26181120085	26181140085
90				26181080090	26181100090	26181120090	26181140090
95				26181080095	26181100095	26181120095	26181140095
100				26181080100	26181100100	26181120100	26181140100
105				26181080105	26181100105	26181120105	26181140105
110				26181080110	26181100110	26181120110	26181140110
115				26181080115	26181100115	26181120115	26181140115
120				26181080120	26181100120	26181120120	26181140120
125				26181080125	26181100125	26181120125	26181140125
130				26181080130	26181100130	26181120130	26181140130
135				26181080135	26181100135	26181120135	26181140135
140				26181080140	26181100140	26181120140	26181140140
145						26181120145	26181140145
150						26181120150	26181140150
160						26181120160	26181140160
170						26181120170	26181140170
180						26181120180	26181140180
190						26181120190	26181140190
200						26181120200	26181140200
210							
220							
230							
240							
250							

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.




DIN 444B 4.6 KNEVELSCHROEVEN – ELEKTROLYTISCH VERZINKT

DIN 444B 4.6 EYE BOLTS – STEEL ZINC PLATED

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER ELECTOR-ZINGUE

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL VERZINKT



ISO :-
DIN : 444B
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P		2	2,5	2,5	2,5	3	3
	1	38	42	46	50	54	60
b	2	44	48	52	56	60	66
	3	57	61	65	69	73	79
d2 (H9)		16	18	18	18	22	25
d3 (max.)		32	32	40	42	45	50
S (max.)		17	20	22	24	25	27
d		M16	M18	M20	M22	M24	M27
LENGTE							
25							
30							
35							
40							
45							
50							
55							
60		26181160060	26181180060	26181200060			
65		26181160065	26181180065	26181200065			
70		26181160070	26181180070	26181200070			
75		26181160075	26181180075	26181200075			
80		26181160080	26181180080	26181200080	26181220080	26181240080	
85		26181160085	26181180085	26181200085	26181220085	26181240085	
90		26181160090	26181180090	26181200090	26181220090	26181240090	
95		26181160095	26181180095	26181200095	26181220095	26181240095	
100		26181160100	26181180100	26181200100	26181220100	26181240100	
105		26181160105	26181180105	26181200105	26181220105	26181240105	
110		26181160110	26181180110	26181200110	26181220110	26181240110	
115		26181160115	26181180115	26181200115	26181220115	26181240115	
120		26181160120	26181180120	26181200120	26181220120	26181240120	26181270120
125		26181160125	26181180125	26181200125	26181220125	26181240125	26181270125
130		26181160130	26181180130	26181200130	26181220130	26181240130	26181270130
135		26181160135	26181180135	26181200135	26181220135	26181240135	26181270135
140		26181160140	26181180140	26181200140	26181220140	26181240140	26181270140
145		26181160145	26181180145	26181200145	26181220145	26181240145	26181270145
150		26181160150	26181180150	26181200150	26181220150	26181240150	26181270150
160		26181160160	26181180160	26181200160	26181220160	26181240160	26181270160
170		26181160170	26181180170	26181200170	26181220170	26181240170	26181270170
180		26181160180	26181180180	26181200180	26181220180	26181240180	26181270180
190		26181160190	26181180190	26181200190	26181220190	26181240190	26181270190
200		26181160200	26181180200	26181200200	26181220200	26181240200	26181270200
210				26181200210	26181220210	26181240210	
220				26181200220	26181220220	26181240220	
230				26181200230			
240				26181200240			
250				26181200250			
260				26181200260			
270							
280							
290							

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.




DIN 444B 4.6 KNEVELSCHROEVEN – ELEKTROLYTISCH VERZINKT

DIN 444B 4.6 EYE BOLTS – STEEL ZINC PLATED

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER ELECTOR-ZINGUE

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL VERZINKT



ISO :-
DIN : 444B
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P		3,5	3,5	4	4,5		
	1	66					
b	2	72	78	84	96		
	3	85	91	97	109		
d2 (H9)		28	30	32	38		
d3 (max.)		55	60	65	78		
S (max.)		30	34	38	44		
d		M30	M33	M36	M42		
LENGTE							
100							
105							
110							
115							
120		26181300120	26181330120	26181360120	26181420120		
125		26181300125	26181330125	26181360125	26181420125		
130		26181300130	26181330130	26181360130	26181420130		
135		26181300135	26181330135	26181360135	26181420135		
140		26181300140	26181330140	26181360140	26181420140		
145		26181300145	26181330145	26181360145	26181420145		
150		26181300150	26181330150	26181360150	26181420150		
160		26181300160	26181330160	26181360160	26181420160		
170		26181300170	26181330170	26181360170	26181420170		
180		26181300180	26181330180	26181360180	26181420180		
190		26181300190	26181330190	26181360190	26181420190		
200		26181300200	26181330200	26181360200	26181420200		
210				26181360210	26181420210		
220				26181360220	26181420220		
230				26181360230	26181420230		
240				26181360240	26181420240		
250				26181360250	26181420250		
260				26181360260	26181420260		
270							
280							
290							

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.

