


## DIN 444B 4.6 KNEVELSCHROEVEN MET VLAKKE ZIJDEN - STAAL

DIN 444B 4.6 EYE BOLTS – STEEL

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL



ISO :-  
DIN : 444B  
NEN : 2310 B  
ANSI :-  
BS :-  
NF :-



**M**  
**St**  
**4.6**

P		0,8	1	1,25	1,5	1,75	2
1		16	18	22	26	30	34
b	2	-	-	28	32	36	40
	3	-	-	-	-	49	53
d2 (H9)		5	6	8	10	12	14
d3 (max.)		12	14	18	20	25	28
S (max.)		6	7	9	12	14	16
d	LENGTE	M5	M6	M8	M10	M12	M14
25		26180050025	26180060025		26180100025	26180120025	
30		26180050030	26180060030		26180100030	26180120030	
35		26180050035	26180060035	26180080035	26180100035	26180120035	
40		26180050040	26180060040	26180080040	26180100040	26180120040	26180140040
45			26180060045	26180080045	26180100045	26180120045	26180140045
50			26180060050	26180080050	26180100050	26180120050	26180140050
55			26180060055	26180080055	26180100055	26180120055	26180140055
60			26180060060	26180080060	26180100060	26180120060	26180140060
65			26180060065	26180080065	26180100065	26180120065	26180140065
70			26180060070	26180080070	26180100070	26180120070	26180140070
75			26180060075	26180080075	26180100075	26180120075	26180140075
80			26180060080	26180080080	26180100080	26180120080	26180140080
85				26180080085	26180100085	26180120085	26180140085
90				26180080090	26180100090	26180120090	26180140090
95				26180080095	26180100095	26180120095	26180140095
100				26180080100	26180100100	26180120100	26180140100
105				26180080105	26180100105	26180120105	26180140105
110				26180080110	26180100110	26180120110	26180140110
115				26180080115	26180100115	26180120115	26180140115
120				26180080120	26180100120	26180120120	26180140120
125				26180080125	26180100125	26180120125	26180140125
130				26180080130	26180100130	26180120130	26180140130
135				26180080135	26180100135	26180120135	26180140135
140				26180080140	26180100140	26180120140	26180140140
145						26180120145	26180140145
150						26180120150	26180140150
160						26180120160	26180140160
170						26180120170	26180140170
180						26180120180	26180140180
190						26180120190	26180140190
200						26180120200	26180140200
210							
220							
230							
240							
250							

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.




## DIN 444B 4.6 KNEVELSCHROEVEN MET VLAKKE ZIJDEN - STAAL

DIN 444B 4.6 EYE BOLTS – STEEL

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL



ISO :-  
DIN : 444B  
NEN : 2310 B  
ANSI :-  
BS :-  
NF :-



**M**  
**St**  
**4.6**

P	1	2	2,5	2,5	2,5	3	3
b	2	44	48	52	56	60	66
	3	57	61	65	69	73	79
d2 (H9)		16	18	18	18	22	25
d3 (max.)		32	32	40	42	45	50
S (max.)		17	20	22	24	25	27
d	LENGTE	M16	M18	M20	M22	M24	M27
25							
30							
35							
40		26180160040	26180180040				
45		26180160045	26180180045				
50		26180160050	26180180050				
55		26180160055	26180180055				
60		26180160060	26180180060	26180200060			
65		26180160065	26180180065	26180200065			
70		26180160070	26180180070	26180200070			
75		26180160075	26180180075	26180200075			
80		26180160080	26180180080	26180200080	26180220080	26180240080	
85		26180160085	26180180085	26180200085	26180220085	26180240085	
90		26180160090	26180180090	26180200090	26180220090	26180240090	
95		26180160095	26180180095	26180200095	26180220095	26180240095	
100		26180160100	26180180100	26180200100	26180220100	26180240100	
105		26180160105	26180180105	26180200105	26180220105	26180240105	
110		26180160110	26180180110	26180200110	26180220110	26180240110	
115		26180160115	26180180115	26180200115	26180220115	26180240115	
120		26180160120	26180180120	26180200120	26180220120	26180240120	26180270120
125		26180160125	26180180125	26180200125	26180220125	26180240125	26180270125
130		26180160130	26180180130	26180200130	26180220130	26180240130	26180270130
135		26180160135	26180180135	26180200135	26180220135	26180240135	26180270135
140		26180160140	26180180140	26180200140	26180220140	26180240140	26180270140
145		26180160145	26180180145	26180200145	26180220145	26180240145	26180270145
150		26180160150	26180180150	26180200150	26180220150	26180240150	26180270150
160		26180160160	26180180160	26180200160	26180220160	26180240160	26180270160
170		26180160170	26180180170	26180200170	26180220170	26180240170	26180270170
180		26180160180	26180180180	26180200180	26180220180	26180240180	26180270180
190		26180160190	26180180190	26180200190	26180220190	26180240190	26180270190
200		26180160200	26180180200	26180200200	26180220200	26180240200	26180270200
210				26180200210	26180220210	26180240210	
220				26180200220	26180220220	26180240220	
230				26180200230			
240				26180200240			
250				26180200250			
260				26180200260			
270							
280							
290							

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.




## DIN 444B 4.6 KNEVELSCHROEVEN MET VLAKKE ZIJDEN - STAAL

DIN 444B 4.6 EYE BOLTS – STEEL

DIN 444B 4.6 CORPS DE BOULON A OEIL – ACIER

DIN 444B 4.6 AUGENSCHRAUBEN – STAHL



ISO :-  
DIN : 444B  
NEN : 2310 B  
ANSI :-  
BS :-  
NF :-



**M**  
**St**  
**4.6**

P		3,5	3,5	4	4,5
1		66			
b	2	72	78	84	96
	3	85	91	97	109
d2 (H9)		28	30	32	38
d3 (max.)		55	60	65	78
S (max.)		30	34	38	44
<b>d</b>		<b>M30</b>	<b>M33</b>	<b>M36</b>	<b>M42</b>
<b>LENGTE</b>					
100					
105					
110					
115					
120		26180300120	26180330120	26180360120	26180420120
125		26180300125	26180330125	26180360125	26180420125
130		26180300130	26180330130	26180360130	26180420130
135		26180300135	26180330135	26180360135	26180420135
140		26180300140	26180330140	26180360140	26180420140
145		26180300145	26180330145	26180360145	26180420145
150		26180300150	26180330150	26180360150	26180420150
160		26180300160	26180330160	26180360160	26180420160
170		26180300170	26180330170	26180360170	26180420170
180		26180300180	26180330180	26180360180	26180420180
190		26180300190	26180330190	26180360190	26180420190
200		26180300200	26180330200	26180360200	26180420200
210				26180360210	26180420210
220				26180360220	26180420220
230				26180360230	26180420230
240				26180360240	26180420240
250				26180360250	26180420250
260				26180360260	26180420260
270					
280					
290					

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

1: L ≤ 125 mm.

2: 125 mm < L ≤ 200 mm.

3: L > 200 mm.

