


DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – ELEKTROLYTISCH VERZINKT

DIN 444LB 4.6 EYE BOLTS FULLY THREADED – STEEL ZINC PLATED

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU'A PROXIMITE DE LA OEIL – ACIER ELECTOR-ZINGUE

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGEN – STAHL VERZINKT



ISO :-
DIN : 444LB
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	0,8	1	1,25	1,5	1,75	2
Lg (max.)	11	14	16	18	23	25
d2 (H9)	5	6	8	10	12	14
d3 (max.)	12	14	18	20	25	28
S (max.)	6	7	9	12	14	16
d	M5	M6	M8	M10	M12	M14
LENGTE						
25	26182050025					
30	26182050030	26182060030				
35	26182050035	26182060035				
40	26182050040	26182060040		26182100040		
45		26182060045		26182100045		
50	26182050050	26182060050	26182080050	26182100050		
55		26182060055	26182080055	26182100055		
60		26182060060	26182080060	26182100060	26182120060	26182140060
65			26182080065	26182100065	26182120065	26182140065
70			26182080070	26182100070	26182120070	26182140070
75			26182080075	26182100075	26182120075	26182140075
80			26182080080	26182100080	26182120080	26182140080
85			26182080085	26182100085	26182120085	26182140085
90			26182080090	26182100090	26182120090	26182140090
95			26182080095	26182100095	26182120095	26182140095
100			26182080100	26182100100	26182120100	26182140100
105				26182100105	26182120105	26182140105
110				26182100110	26182120110	26182140110
115				26182100115	26182120115	26182140115
120				26182100120	26182120120	26182140120
125				26182100125	26182120125	26182140125
130				26182100130	26182120130	26182140130
135				26182100135	26182120135	26182140135
140				26182100140	26182120140	26182140140
145						
150						
160						
170						
180						
190						
200						
210						
220						
230						
240						
250						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.




DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – ELEKTROLYTISCH VERZINKT

DIN 444LB 4.6 EYE BOLTS FULLY THREADED – STEEL ZINC PLATED

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU'À PROXIMITE DE LA OEIL – ACIER ELECTOR-ZINGUE

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGEN – STAHL VERZINKT



ISO :-
DIN : 444LB
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	2	2,5	2,5	2,5	3	3
Lg (max.)	27	30	32	35	40	42
d2 (H9)	16	18	18	18	22	25
d3 (max.)	32	32	40	42	45	50
S (max.)	17	20	22	24	25	27
d	M16	M18	M20	M22	M24	M27
LENGTE						
25						
30						
35						
40						
45						
50						
55						
60						
65						
70	26182160070	26182180070	26182200070			
75	26182160075	26182180075	26182200075			
80	26182160080	26182180080	26182200080	26182220080	26182240080	
85	26182160085	26182180085	26182200085	26182220085	26182240085	
90	26182160090	26182180090	26182200090	26182220090	26182240090	
95	26182160095	26182180095	26182200095	26182220095	26182240095	
100	26182160100	26182180100	26182200100	26182220100	26182240100	
105	26182160105	26182180105	26182200105	26182220105	26182240105	
110	26182160110	26182180110	26182200110	26182220110	26182240110	
115	26182160115	26182180115	26182200115	26182220115	26182240115	
120	26182160120	26182180120	26182200120	26182220120	26182240120	26182270120
125	26182160125	26182180125	26182200125	26182220125	26182240125	26182270125
130	26182160130	26182180130	26182200130	26182220130	26182240130	26182270130
135	26182160135	26182180135	26182200135	26182220135	26182240135	26182270135
140	26182160140	26182180140	26182200140	26182220140	26182240140	26182270140
145	26182160145	26182180145	26182200145	26182220145	26182240145	26182270145
150	26182160150	26182180150	26182200150	26182220150	26182240150	26182270150
160	26182160160	26182180160	26182200160	26182220160	26182240160	26182270160
170	26182160170	26182180170	26182200170	26182220170	26182240170	26182270170
180	26182160180	26182180180	26182200180	26182220180	26182240180	26182270180
190	26182160190	26182180190	26182200190	26182220190	26182240190	26182270190
200	26182160200	26182180200	26182200200	26182220200	26182240200	26182270200
210						
220						
230						
240						
250						
260						
270						
280						
290						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.




DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – ELEKTROLYTISCH VERZINKT

DIN 444LB 4.6 EYE BOLTS FULLY THREADED– STEEL ZINC PLATED

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU’A PROXIMITE DE LA OEIL – ACIER ELECTOR-ZINGUE

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGE – STAHL VERZINKT



ISO :-
DIN : 444B
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	3,5	3,5	4	4,5		
Lg (max.)	46	54	59	65		
d2 (H9)	28	30	32	38		
d3 (max.)	55	60	65	78		
S (max.)	30	34	38	44		
d	M30	M33	M36	M42		
LENGTE						
100						
105						
110						
115						
120	26182300120	26182330120	26182360120	26182420120		
125	26182300125	26182330125	26182360125	26182420125		
130	26182300130	26182330130	26182360130	26182420130		
135	26182300135	26182330135	26182360135	26182420135		
140	26182300140	26182330140	26182360140	26182420140		
145	26182300145	26182330145	26182360145	26182420145		
150	26182300150	26182330150	26182360150	26182420150		
160	26182300160	26182330160	26182360160	26182420160		
170	26182300170	26182330170	26182360170	26182420170		
180	26182300180	26182330180	26182360180	26182420180		
190	26182300190	26182330190	26182360190	26182420190		
200	26182300200	26182330200	26182360200	26182420200		
210						
220						
230						
240						
250						
260						
270						
280						
290						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

