


DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – STAAL

DIN 444LB 4.6 EYE BOLTS FULLY THREADED– STEEL

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU'À PROXIMATE DE LA OEIL – ACIER

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGE – STAHL



ISO :-
DIN : 444LB
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	0,8	1	1,25	1,5	1,75	2
Lg (max.)	11	14	16	18	23	25
d2 (H9)	5	6	8	10	12	14
d3 (max.)	12	14	18	20	25	28
S (max.)	6	7	9	12	14	16
d	M5	M6	M8	M10	M12	M14
LENGTE						
25	26185050025					
30	26185050030	26185060030				
35	26185050035	26185060035				
40	26185050040	26185060040		26185100040		
45		26185060045		26185100045		
50	26185050050	26185060050	26185080050	26185100050		
55		26185060055	26185080055	26185100055		
60		26185060060	26185080060	26185100060	26185120060	26185140060
65			26185080065	26185100065	26185120065	26185140065
70			26185080070	26185100070	26185120070	26185140070
75			26185080075	26185100075	26185120075	26185140075
80			26185080080	26185100080	26185120080	26185140080
85			26185080085	26185100085	26185120085	26185140085
90			26185080090	26185100090	26185120090	26185140090
95			26185080095	26185100095	26185120095	26185140095
100			26185080100	26185100100	26185120100	26185140100
105				26185100105	26185120105	26185140105
110				26185100110	26185120110	26185140110
115				26185100115	26185120115	26185140115
120				26185100120	26185120120	26185140120
125				26185100125	26185120125	26185140125
130				26185100130	26185120130	26185140130
135				26185100135	26185120135	26185140135
140				26185100140	26185120140	26185140140
145						
150						
160						
170						
180						
190						
200						
210						
220						
230						
240						
250						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.




DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – STAAL

DIN 444LB 4.6 EYE BOLTS FULLY THREADED – STEEL

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU'À PROXIMATE DE LA OEIL – ACIER

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGEN – STAHL



ISO :-
DIN : 444LB
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	2	2,5	2,5	2,5	3	3
Lg (max.)	27	30	32	35	40	42
d2 (H9)	16	18	18	18	22	25
d3 (max.)	32	32	40	42	45	50
S (max.)	17	20	22	24	25	27
d	M16	M18	M20	M22	M24	M27
LENGTE						
25						
30						
35						
40						
45						
50						
55						
60						
65						
70	26185160070	26185180070	26185200070			
75	26185160075	26185180075	26185200075			
80	26185160080	26185180080	26185200080	26185220080	26185240080	
85	26185160085	26185180085	26185200085	26185220085	26185240085	
90	26185160090	26185180090	26185200090	26185220090	26185240090	
95	26185160095	26185180095	26185200095	26185220095	26185240095	
100	26185160100	26185180100	26185200100	26185220100	26185240100	
105	26185160105	26185180105	26185200105	26185220105	26185240105	
110	26185160110	26185180110	26185200110	26185220110	26185240110	
115	26185160115	26185180115	26185200115	26185220115	26185240115	
120	26185160120	26185180120	26185200120	26185220120	26185240120	26185270120
125	26185160125	26185180125	26185200125	26185220125	26185240125	26185270125
130	26185160130	26185180130	26185200130	26185220130	26185240130	26185270130
135	26185160135	26185180135	26185200135	26185220135	26185240135	26185270135
140	26185160140	26185180140	26185200140	26185220140	26185240140	26185270140
145	26185160145	26185180145	26185200145	26185220145	26185240145	26185270145
150	26185160150	26185180150	26185200150	26185220150	26185240150	26185270150
160	26185160160	26185180160	26185200160	26185220160	26185240160	26185270160
170	26185160170	26185180170	26185200170	26185220170	26185240170	26185270170
180	26185160180	26185180180	26185200180	26185220180	26185240180	26185270180
190	26185160190	26185180190	26185200190	26185220190	26185240190	26185270190
200	26185160200	26185180200	26185200200	26185220200	26185240200	26185270200
210						
220						
230						
240						
250						
260						
270						
280						
290						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.




DIN 444LB 4.6 KNEVELSCHROEVEN VOLDRAAD – STAAL

DIN 444LB 4.6 EYE BOLTS FULLY THREADED– STEEL

DIN 444LB 4.6 CORPS DE BOULON A OEIL FILETEES JUSQU’A PROXIMATE DE LA OEIL – ACIER

DIN 444LB 4.6 AUGENSCHRAUBEN MIT GEWINDE BIS AUGE – STAHL



ISO :-
DIN : 444B
NEN : 2310 B
ANSI :-
BS :-
NF :-



M
St
4.6

P	3,5	3,5	4	4,5		
Lg (max.)	46	54	59	65		
d2 (H9)	28	30	32	38		
d3 (max.)	55	60	65	78		
S (max.)	30	34	38	44		
d	M30	M33	M36	M42		
LENGTE						
100						
105						
110						
115						
120	26185300120	26185330120	26185360120	26185420120		
125	26185300125	26185330125	26185360125	26185420125		
130	26185300130	26185330130	26185360130	26185420130		
135	26185300135	26185330135	26185360135	26185420135		
140	26185300140	26185330140	26185360140	26185420140		
145	26185300145	26185330145	26185360145	26185420145		
150	26185300150	26185330150	26185360150	26185420150		
160	26185300160	26185330160	26185360160	26185420160		
170	26185300170	26185330170	26185360170	26185420170		
180	26185300180	26185330180	26185360180	26185420180		
190	26185300190	26185330190	26185360190	26185420190		
200	26185300200	26185330200	26185360200	26185420200		
210						
220						
230						
240						
250						
260						
270						
280						
290						

Knevelschroeven M14, M18 en M22 zijn niet meer in de actuele norm omschreven.

