



## ACS-400

Thin-wall heat shrink tubing / flexible / flame retardant / 4:1 / mil spec 135 degrees

### Features:

- Crosslinked Polyolefin • Shrink ratio: 4:1 • Flame retardant • High flexibility

### Approvals:

- UL224 125 °C VW-1 600 V file E526134 • CSA C22.2 No. 198.1-06
- Meets: RoHS • Meets: SAE-AMS-DTL-23053/5 class 1 and 2

### Application:

- Operating temperature: -55 °C to +135 °C • Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C • Longitudinal change: 0 ± 10% max.

### Order information:

- Color: black



For electronic, automotive and consumer goods.

Flexible, flame retardant, low shrinking temperature.

Free from harmful substances such as PBB's, PBBO's, PBBE's.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in mm
ACS-400 - 19,1/4,6	19,1	4,6	1,7	1220
ACS-400 - 25,4/7,0	25,4	7,0	1,7	1220
ACS-400 - 38,1/9,5	38,1	9,5	1,7	1220
ACS-400 - 50,8/14,0	50,8	14,0	1,7	1220
ACS-400 - 76,2/20,6	76,2	20,6	1,7	1220
ACS-400 - 102,0/26,7	102,0	26,7	1,7	1220
ACS-400 - 115,0/36,8	115,0	36,8	1,7	1220

For cross references, please see pages 4-5