



HEAVY WALL TUBING

AHWA-6X

Flexible flame retardant, high shrink ratio



AHWA-6X

Heavy-wall heat shrink tubing / with hot melt adhesive and extra high shrink ratio

Features:

- Heavy-wall tubing with hot melt adhesive • Shrink ratio: 6:1 • Crosslinked Polyolefin
- Excellent sealing properties • Extra heavy-wall • UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C • Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black



The high shrink ratio provides close fit to a wide variety of irregular shapes connector and figurations.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in mm
AHWA-6X 19,0/3,2	19,0	3,2	3,2	1220
AHWA-6X 33,0/5,5	33,0	5,5	3,4	1220
AHWA-6X 44,4/7,4	44,4	7,4	3,6	1220
AHWA-6X 50,8/8,3	50,8	8,3	4,7	1220
AHWA-6X 69,8/11,7	69,8	11,7	4,7	1220
AHWA-6X 88,9/17,1	88,9	17,1	4,7	1220
AHWA-6X 119,4/22,9	119,4	22,9	4,7	1220
AHWA-6X 235,0/40,0	235,0	40,0	4,7	1220

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.