



AMW/AMWA

Medium-wall heat shrink tubing / with and without hot melt adhesive

Features:

- Medium-wall tubing with and without hot melt adhesive
- Good environmental protection
- Good electrical and mechanical performance
- Ideal for low voltage applications
- UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Also available in lengths of 1 and 1,5 meter
- Color: black



Recommended to applications for light cable and wire harnesses that require waterproofing, protection, and sealing of connectors components within the tubing.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in mm
AMW/AMWA 8/2	8,0	2,0	1,6	1220
AMW/AMWA 12/3	12,0	3,0	2,0	1220
AMW/AMWA 16/5	16,0	5,0	2,2	1220
AMW/AMWA 22/6	22,0	6,0	2,4	1220
AMW/AMWA 28/6	28,0	6,0	2,5	1220
AMW/AMWA 33/8	33,0	8,0	2,5	1220
AMW/AMWA 40/12	40,0	12,0	2,5	1220
AMW/AMWA 55/16	55,0	16,0	2,7	1220
AMW/AMWA 65/19	65,0	19,0	2,9	1220
AMW/AMWA 75/22	75,0	22,0	3,0	1220
AMW/AMWA 85/25	85,0	25,0	3,0	1220
AMW/AMWA 95/25	95,0	25,0	3,0	1220
AMW/AMWA 115/34	115,0	34,0	3,2	1220
AMW/AMWA 140/42	140,0	42,0	3,3	1220
AMW/AMWA 160/50	160,0	50,0	3,3	1220
AMW/AMWA 180/58	180,0	58,0	3,3	1220
AMW/AMWA 205/65	205,0	65,0	3,3	1220
AMW/AMWA 235/65	235,0	65,0	3,7	1220
AMW/AMWA 265/75	265,0	75,0	3,8	1220
AMW/AMWA 300/75	300,0	75,0	3,8	1220
AMW/AMWA 350/100	350,0	100,0	4,2	1220
AMW/AMWA 380/150	380,0	150,0	4,2	1220
AMW/AMWA 410/150	410,0	150,0	4,2	1220

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.