

HEAT RESISTANT

Material	: Polyamide 6.6 heat resistant
Color	: Transparent (greenish) / black (UV resistant)
Sizes	: Other sizes available on request
Temperature range	: -40 °C up to +120 °C
Flammability	: UL 94 V2
Certification	: UL, Lloyd's



Typenr.	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)
HEAT RES. 100x2,5mm	2,5	22	8,1	100 / 1000
HEAT RES. 120x2,5mm	2,5	30	8,1	100 / 1000
HEAT RES. 140x2,5mm	2,5	33	8,1	100 / 1000
HEAT RES. 160x2,5mm	2,5	40	8,1	100 / 1000
HEAT RES. 200x2,5mm	2,5	53	8,1	100 / 1000
HEAT RES. 140x3,6mm	3,6	33	18,2	100 / 1000
HEAT RES. 200x3,6mm	3,6	53	18,2	100 / 1000
HEAT RES. 300x3,6mm	3,6	76	18,2	100 / 1000
HEAT RES. 370x3,6mm	3,6	102	18,2	100 / 1000
HEAT RES. 200x4,8mm	4,8	50	22,2	100 / 1000
HEAT RES. 300x4,8mm	4,8	76	22,2	100 / 1000
HEAT RES. 370x4,8mm	4,8	102	22,2	100
HEAT RES. 430x4,8mm	4,8	110	22,2	100
HEAT RES. 200x7,6mm	7,6	50	54,4	100
HEAT RES. 300x7,6mm	7,6	76	54,4	100
HEAT RES. 370x7,6mm	7,6	102	54,4	100

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.