

POLYPROP

Material	: Polypropylene
Color	: Green
Temperature range	: -35 °C up to +85 °C
Properties	: Acid resistant, floats, UV resistant
Flammability	: UL 94 HB



Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)
POLYPROP. 100x2,5mm	100	2,5	22	4,0	100
POLYPROP. 140x3,6mm	140	3,6	33	9,0	100
POLYPROP. 190x4,8mm	190	4,8	46	14,0	100
POLYPROP. 200x4,8mm	200	4,8	50	14,0	100
POLYPROP. 300x4,8mm	300	4,8	76	14,0	100
POLYPROP. 370x4,8mm	370	4,8	102	14,0	100
POLYPROP. 200x7,6mm	200	7,6	50	22,2	100
POLYPROP. 370x7,6mm	370	7,6	102	22,2	100

TEFZEL®

Material	: Tefzel® E/TFE (Ethylene-tetrafluorethylene)
Color	: Aquamarine blue
Temperature range	: -46 °C up to +150 °C
Flammability	: UL 94 V0
Certification	: RoHS
Resistency	: UV, chemical fluids, : radiation: 200 Mrad EEE383/323



Typenr.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Packing (pcs)
TEFZEL 100x2,5mm	100	2,5	22	8,1	100
TEFZEL 150x3,6mm	150	3,6	35	18,2	100
TEFZEL 200x3,6mm	200	3,6	53	18,2	100
TEFZEL 200x4,8mm	200	4,6	50	22,2	100
TEFZEL 300x4,8mm	300	4,8	76	22,2	100
TEFZEL 370x4,8mm	370	4,8	102	22,2	100
TEFZEL 300x7,6mm	300	7,3	76	54,4	100
TEFZEL 370x7,6mm	370	7,4	102	54,4	100
TEFZEL 430x9,0mm	430	8,8	110	79,4	100

There is a minimum order quantity for Tefzel® cable ties

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.