



HHWA

Heavy-wall heat shrink tubing / with hot melt adhesive (co-extrusion)

Features:

- Heavy-wall tubing with hot melt adhesive • Co-extrusion technology
- Excellent electrical and mechanical performance • UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C • Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Also available in lengths of 1 and 1,5 meter
- Color: black



Recommended for applications on light cables and wire harnesses which require waterproofing, protection of connector components. Halogen and Cadmium free.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in mm
HHWA 9/3	9,0	3,0	1,95	1220
HHWA 15/4	15,0	4,0	2,35	1220
HHWA 20/6	20,0	6,0	2,45	1220
HHWA 33/8	33,0	8,0	3,15	1220
HHWA 43/12	43,0	12,0	4,05	1220
HHWA 51/16	51,0	16,0	4,05	1220
HHWA 75/22	75,0	22,0	4,20	1220
HHWA 85/25	85,0	25,0	4,20	1220
HHWA 95/25	95,0	25,0	4,20	1220
HHWA 105/25	105,0	25,0	4,20	1220
HHWA 115/34	115,0	34,0	4,20	1220
HHWA 130/36	130,0	36,0	4,20	1220

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.