



PO 2:1

Semi Rigid, Glossy Colors, Halogen Free

Excellent and durable shrink tubing that can be used for electrical insulation, annotation, protection and much more.

Made of semi-flexible Halogen-free Polyolefin, available in many colors. This shrink tubing has a nice glossy surface that enhances the colors.



Product Information	
Material:	Polyolefin, Halogen free
Shrink ratio:	2:1
Shrink temperature:	120°C
Temperature range:	-55°C to 110°C
Standard colours:	Clear, black, orange, violet, brown, green, white, red, grey, yellow, blue.
Standard spools:	See chart
Dielectric strength:	>20 kV
Approvals:	ROHS

Type	Dimensions		Thickness - fully shrunk	Spool Length m
	Before shrink	After shrink		
1,2	1,2	0,6	0,40	300
1,6	1,6	0,8	0,40	300
2,4	2,4	1,2	0,45	150
3,2	3,2	1,6	0,45	150
4,0	4,0	2,0	0,45	100
4,8	4,8	2,4	0,45	60
6,4	6,4	3,2	0,45	60
8,0	8,0	4,0	0,55	60
9,5	9,5	5,0	0,55	60
12,7	12,7	6,4	0,65	60
16,0	16,0	8,0	0,70	60
19,1	19,1	10,2	0,75	60
25,4	25,4	12,7	0,85	60
31,8	31,8	15,9	1,30	60
38,1	38,1	15,9	1,30	60
50,8	50,8	15,9	1,30	60
76,2	76,2	38,1	1,27	60
101,2	101,2	50,8	1,40	30
126,0	126,0	60,0	1,30	30
152,0	152,0	75,0	1,30	30
186,0	186,0			

With the exception of spool lengths in metres (m), all dimensions are in millimetres. Other dimensions, lengths and colours on request.

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.