



BUSBAR INSULATION TUBING

ABBH

Halogen free busbar insulation tubing



ABBH

Halogen free flexible busbar insulation tubing

Features:

- ABBH = heavy-wall tubing • Heavy-wall flexible busbar insulation tubing
- Modified Polyolefin • Excellent electrical properties and creeping resistance
- Halogen free • UV and weather resistant • Up to 36 kV

Approvals:

- Meets: RoHS

Application:

- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: red



Provides insulation enhancement and protection against flashover and accidentally induced discharge

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Reel / Meter & Standard length in mm
ABBH 25/10	25,0	10,0	4,0	1220 mm
ABBH 40/16	40,0	16,0	4,0	1220 mm
ABBH 50/20	50,0	20,0	4,0	1220 mm
ABBH 75/25	75,0	25,0	4,0	1220 mm
ABBH 95/30	95,0	30,0	4,0	1220 mm
ABBH 120/40	120,0	40,0	4,1	1220 mm
ABBH 180/58	180,0	58,0	4,1	1220 mm

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.