



BUSBAR INSULATION TUBING

ABM

Halogen free busbar insulation tubing



ABM

Halogen free busbar insulation tubing

Features:

- Medium-wall halogen free busbar insulation tubing • Crosslinked Polyolefin
- Excellent electrical properties and creeping resistance • UV resistant
- Up to 36 kV

Approvals:

- Meets: RoHS

Application:

- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: red



Provides insulation enhancement and protection against flashover and accidentally induced discharge

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Reel / Meter & Standard length in mm
ABM 19/6	19,0	6,0	1,9	30 meter
ABM 25/10	25,0	10,0	1,9	30 meter
ABM 30/12	30,0	12,0	1,9	30 meter
ABM 35/14	35,0	14,0	1,9	30 meter
ABM 40/16	40,0	16,0	1,9	30 meter
ABM 50/20	50,0	20,0	1,9	30 meter
ABM 65/25	65,0	25,0	1,9	30 meter
ABM 75/30	75,0	30,0	1,9	15 meter
ABM 100/40	100,0	40,0	1,9	15 meter
ABM 120/50	120,0	50,0	2,9	1000 mm
ABM 150/60	150,0	60,0	2,9	1000 mm
ABM 180/60	180,0	60,0	2,9	1000 mm
ABM 205/75	205,0	75,0	2,9	1000 mm

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.